

Pin-Lug Couplings

Glass-filled Nylon

FEATURES

- Temperature range under normal conditions -30°F to 200°F
- Polyethylene gasket included
- Easy hand tightening



DESCRIPTION	Female Part No.	Male Part No.	Set Part No.
1-1/2"	150 PLF-N	150 PLM-N	150 PLS-N
2"	200 PLF-N	200 PLM-N	200 PLS-N
3"	300 PLF-N	300 PLM-N	300 PLS-N
4"	400 PLF-N	400 PLM-N	400 PLS-N

Size	Operating Pressure
1-1/2" - 2"	150 psi max @ 70°F
3"	125 psi max @ 70°F
4"	100 psi max @ 70°F

Hose Mender

Glass-filled Nylon

FEATURES

- Fast, easy installation
- Exceptionally strong and durable
- Non-conducting
- Chemical resistant, will not rust



DESCRIPTION	Part No.
1-1/2"	150 HM-N
2"	200 HM-N



Switch Adapters

Glass-filled Polypropylene

FEATURES

- Permits quick changing of spray nozzles
- Self-aligning grooves
- Two-piece adapter



DESCRIPTION	Part No.
3/4" x 1/4"	61326
3/4" x 3/8"	61327

Operating Pressure
125 psi max @ 70°F



Polypropylene Pipe Caps and Water Tank Caps

FEATURES

- Heat and mildew resistant
- Corrosion resistant, will not seize
- Impervious to ultra-violet rays
- Water tank cap is Type 100 3-way, reinforced polypropylene



DESCRIPTION	2"	2-1/2"	3"	4"
Polypropylene pipe cap	200PC-M		300PC-M	400PC-M
Polypropylene water tank cap		MP W100		
"3-ways are 3/4" FPT"				

