

Heavy Duty Threaded Polypropylene Fittings

FEATURES

- Schedule 80 design.
- Manufactured from glass-reinforced polypropylene for strength and durability.
- Chemical resistant to most acids (Refer to chemical resistance tables for specific recommendation)
- Temperature range 10° F–180° F.

Operating Pressure:
 120 psi max @ 0° F
 150 psi max @ 70° F
 80 psi max @ 150° F



A

TEES

ITEM	DESCRIPTION	PART NUMBER
A	1/2"	70800
A	3/4"	70801
A	1"	70802
A	1-1/4"	70803
A	1-1/2"	70804
A	2"	70805
A	3"	70806

Price
Lookup

90° STREET ELBOWS

ITEM	DESCRIPTION	PART NUMBER
C	1/2"	70814
C	3/4"	70815
C	1"	70816
C	1-1/4"	70817
C	1-1/2"	70818
C	2"	70819
C	3"	70820

Price
Lookup



C



B

90° PIPE ELBOWS

ITEM	DESCRIPTION	PART NUMBER
B	1/2"	70807
B	3/4"	70808
B	1"	70809
B	1-1/4"	70810
B	1-1/2"	70811
B	2"	70812
B	3"	70813

Price
Lookup

CROSSES

ITEM	DESCRIPTION	PART NUMBER
D	3/4"	70821
D	1"	70822
D	1-1/4"	70823
D	1-1/2"	70824
D	2"	70825

Price
Lookup



D

