

## AIR BRAKE - ACCESSORIES

BRASS SPLIT SLEEVE DOT  
FITTINGS (5/32 O.D.)

## COLLET



Part #	Tube O.D.	List Price
38-711	5/32"	1.13

## NUT



Part #	Tube O.D.	List Price
38-732	5/32"	1.47

## DOUBLE END UNION



Part #	Tube O.D.	List Price
38-761	5/32"	12.47

## CONNECTOR



Part #	Tube O.D.	Pipe Thread	List Price
38-769	5/32"	1/16	7.59
38-770	5/32"	1/8	7.73

## ELBOW



Part #	Tube	Pipe Thread	List Price
38-718	5/32"	1/8	7.27

## BRASS FITTINGS

## AIR BRAKE TUBING

- SAE J844, Type 3 A & B & DOT FMVSS 106
- Nylon inner tube with open ply nylon fiber reinforcement and nylon cover.
- 40° F to +200° F temperature range.
- 150 P.S.I. max. working pressure



Part #	Type A	Color	Length	List Price
38-950	1/8"	Black	100'	45.53
38-952	1/4"	Black	100'	79.35
38-952R	1/4"	Red	100'	124.95
38-952U	1/4"	Blue	100'	124.95
38-952-2	1/4"	Black	500'	551.25
38-952-3	1/4"	Black	1000'	955.50

## AIR BRAKE TUBING

Part #	Type B	Color	Length	List Price
38-960	3/8"	Black	100'	156.57
38-960U	3/8"	Blue	100'	338.10
38-960Y	3/8"	Yellow	100'	338.10
38-960B5	3/8"	Black	500'	723.33
38-965	1/2"	Black	100'	209.14
38-965R	1/2"	Red	100'	463.05
38-965B5	1/2"	Black	500'	986.19
38-970	5/8"	Black	100'	529.20
38-975	3/4"	Black	100'	690.90

NOTE: The Synflex, Parker and Eaton tubing must be torqued at 47 in. pounds.

Any other 5/32 DOT tubing used, tubing or fitting manufacturer should be contacted for proper torque requirements.

## FUEL LINE AND VAPOR EMISSION



- SAE 30R7
- Nitrile tube w/ spiral synthetic cord, hypalon cover.
- 50 p.s.i. working pressure. 1/2 -35 PSI
- 40° F to + 257° F temperature range.
- Low pressure/ high temperature fuel for cars, light trucks, and small engines.
- Meets SAE J1402

Part #	ID	OD	Length	List Price
38-920	3/16	13/32	25'	128.63
38-926	5/16	9/16	25'	152.51
38-923	1/4	1/2	25'	135.98
38-927	3/8	5/8	50'	99.78

**MIDLAND  
METAL**