



7363

## SUPER-FLEX®

### Material Suction Hose

#### Series 7363

Designed for wet or dry abrasive product transfer service. The highly abrasion resistant tube is also static conductive, eliminating the need for a static wire. The cover is corrugated for flexible handling. This hose is rated for full suction and discharge.

3:1 Design factor

#### >> Tube dissipates static for safety

<b>Tube</b>	Black Natural Rubber Blend, 3/16 in. thick, static conductive
<b>Cover</b>	Black Natural Rubber Blend
<b>Reinforcement</b>	Textile tire cord plies with helix wire
<b>Temperature Range</b>	-40°F to +160°F (-40°C to +71°C)
<b>Branding</b>	PARKER SERIES 7363 SUPER-FLEX® ABRASIVE SUCTION AND DISCHARGE 100 PSI MAX WP MADE IN USA
<b>Brand Description</b>	Tape Brand - White letters
<b>Compare to</b>	Goodyear Plicord HD Vacuum, Diversiflex; Gates 688SB; Titan SW336; Boston Sabertooth

**LENGTHS:** 100 ft.

**COUPLINGS:** For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7363-2000	2	50.8	2	2.740	69.6	159	6.0	100
7363-3000	3	76.2	2	3.800	96.6	246	9.0	100
7363-4000	4	101.6	2	4.875	123.8	360	12.0	100
7363-5000	5	127.0	2	5.929	150.6	501	15.0	100
7363-6000	6	152.4	2	6.937	176.2	560	18.0	100

#### Applications

- Transfer of Material to and from Rail Cars and Barges
- Unloading Hoppers
- Sewer Cleaning



**WARNING!** Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressures.