



DAY-FLO® Heavy Duty Water Discharge Hose Series 7306H

This is the tough one – designed for heavy-duty water discharge applications. The combination of a heavy wall and 200 PSI working pressure rating (150 PSI in 10 in. ID size) make this the right hose for applications that need extra capacity and durability.
3:1 Design factor

>> Durable to handle the toughest conditions

Tube	Black EPDM
Cover	Black EPDM
Reinforcement	Multiple textile plies
Temperature Range	-30°F to +212°F (-34°C to +100°C)
Branding	PARKER SERIES 7306H DAY-FLO H.D. WATER DISCHARGE HOSE XXX PSI MAX WP MADE IN USA 001
Brand Description	Tape Brand - White letters on blue stripe
Compare to	Goodyear Plicord HD Water Discharge; Kuriyama Heavy Water Discharge; Titan HD Water Discharge

LENGTHS: 100 ft. except 10 in., which is 50 ft.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692, 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

7306H

Applications

- Water Discharge

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Max. Rec. WP
7306H-1500	1½	38.0	4	2.032	51.6	85	200
7306H-2000	2	50.8	4	2.536	64.4	114	200
7306H-2500	2½	63.5	4	3.050	77.5	148	200
7306H-3000	3	76.2	4	3.550	90.2	175	200
7306H-4000	4	101.6	4	4.556	115.7	231	200
7306H-5000	5	127.0	4	5.582	141.8	298	200
7306H-6000	6	152.4	4	6.646	168.8	358	200
7306H-8000	8	203.2	4	8.646	219.6	472	200
7306H-10000	10	254.0	4	10.646	270.4	585	150



WARNING! Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressures.