



Heater Hose

Series 7186

Lightweight hose designed for automotive coolant heater hose service. Also ideal for low pressure water discharge. Resistant to LASSO® herbicide.

4:1 Design factor

>> Heat resistant

Tube	Black EPDM
Cover	Black EPDM
Reinforcement	Multiple textile plies
Temperature Range	-40°F to +212°F (-40°C to +100°C)
Branding	PARKER SERIES 7186 HEATER HOSE ½ ID (12.7 MM) MADE IN USA
Brand Description	Ink Brand - White Letter color
Compare to	Thermoid Black Standard Heater

LENGTHS: Random lengths on reels, 550 ft. max, 400 ft. min, max. 3 pieces with min. 50 ft. length.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7628. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7186-501	½	12.7	2	0.781	19.8	18	6.0	125
7186-501050	½	12.7	2	0.781	19.8	18	6.0	125
7186-631	⅝	15.9	2	0.906	23.0	21	8.0	90
7186-631050	⅝	15.9	2	0.906	23.0	21	8.0	90
7186-751	¾	19.1	2	1.031	26.2	25	9.0	70
7186-751050	¾	19.1	2	1.031	26.2	25	9.0	70

7186

Applications

- Automotive Coolant