

HEATER & COOLANT HOSES

6823 X-treme CAC (Charge Air Cooler) Hose Hot Side 500°F



CAC hoses are used in all charge-cooler requirements since they are capable of handling an application that requires movement and misalignment. The hot side handles temperatures up to 500°F.

TUBE COLOR: Brick Red

REINFORCEMENT: None

COVER COLOR: Brick Red

BRANDING: PARKER SILICONE SERIES 6823 (DATE CODE) MADE IN MEXICO

TEMP. RANGE: -65° to +500°F

APPLICATIONS: Turbochargers on engines

SPECIFICATIONS: SAEJ20R5

MAX. WORKING PRESSURE: 1/3 of the Burst Pressure

PART NUMBER	SIZE INCH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH INCHES	BURST PRESSURE PSI	WEIGHT LB/EA
		INCH	MM	INCH	MM			
6823-30006000	3	3.00	76	3.24	82.3	6	80	0.37
6823-35006000	3-1/2	3.50	89	3.74	95.0	6	80	0.43
6823-40006000	4	4.00	102	4.24	107.7	6	80	0.55
6823-40008000	4	4.00	102	4.24	107.7	8	80	0.74

6824 X-treme CAC (Charge Air Cooler) Hose Cold Side 350°F



CAC hoses are used in all charge-cooler requirements since they are capable of handling an application that requires movement and misalignment. The cold side handles temperatures up to 350°F.

TUBE COLOR: Brick Red

REINFORCEMENT: None

COVER COLOR: Blue

BRANDING: PARKER SILICONE SERIES 6824 (DATE CODE) MADE IN MEXICO

TEMP. RANGE: -65° to +350°F

APPLICATIONS: Turbochargers on engines

SPECIFICATIONS: SAEJ20R5

MAX. WORKING PRESSURE: 1/3 of the Burst Pressure

PART NUMBER	SIZE INCH	INSIDE DIAMETER		OUTSIDE DIAMETER		LENGTH INCHES	BURST PRESSURE PSI	WEIGHT LB/EA
		INCH	MM	INCH	MM			
6824-30006000	3	3.00	76	3.32	84.4	6	80	0.52
6824-35006000	3-1/2	3.50	89	3.82	97.1	6	80	0.61
6824-40006000	4	4.00	102	4.32	109.8	6	80	0.70
6824-40008000	4	4.00	102	4.32	109.8	8	80	0.91