

Quick Disconnect Couplings and Hydraulic Valves

DRYBREAK STYLE COUPLINGS



71 Series

Ball-Locking, Push-to-Connect Flush-Face Coupling

- Sizes 1/8" to 2", working pressures to 10,000 psi (690 bar)
- Steel or stainless steel construction
- Flat Face design allows for easy cleaning & minimal air inclusion



74 Series

ISO 16028/HTMA Flush-Face Coupling

- Sizes 1/4" & 1", working pressures to 4,600 psi (317 bar)
- Steel construction
- Connect under pressure capability available



23 Series

Industrial Ball-Locking, Push-to-Connect Dry Break

- Sizes 3/8" & 1/2", working pressures to 3,000 psi (207 bar)
- Steel construction
- Safety sleeve lock as standard to prevent accidental disconnection



78 Series

Thread-to-Connect, Dry Break Coupling

- Sizes 3/4" to 1-1/2", working pressures to 3,000 psi (207 bar)
- Brass construction with steel wing nut or hex nut sleeve
- Interchangeable with Aeroquip 5100 and Parker 6100



28-1 Series

Ball-Locking, Push-to-Connect Military/Aerospace Dry Break

- Sizes 1/4" to 2", working pressures to 1,000 psi (69 bar)
- Aluminum or 316 stainless steel construction
- Performance meets or exceeds MIL-C-25427A & MIL-C-7413B



29 Series

Ball-Locking, Push-to-Connect Military/Aerospace Dry Break

- Sizes 1/8" to 1-1/4", working pressures to 5,500 psi (379 bar)
- Aluminum or 316 Stainless steel construction
- Performance meets or exceeds MIL-C-25427A & MIL-C-7413B



77 Series

Dog-Locking, High Pressure Dry Break

- 1/4" Size, working pressures to 36,000 psi (2483 bar)
- Steel or stainless steel construction
- Internal safety sleeve lock & optional Autoclave end connections



Snap-Tite