

SW369 HARDWALL MARINE EXHAUST HOSE

U.S.C.G. Type Marine hose.



- Ultra-flexible, lightweight hardwall marine exhaust hose specifically designed to be a high temperature, wet exhaust and fuel fill flexible connection.
- Dual helix wire allows for tight bends without kinking.
- Specially formulated cover is heat and ozone resistant.

Tube: Extruded Nitrile.
Reinforcement: Textile with dual wire helix.
Cover: Specially compounded Nitrile.
Temperature: -40° to +200°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1 1/4"	1 11/16"	4"	200	.56	Full
1 3/8"	1 13/16"	4"	200	.59	Full
1 1/2"	2"	5"	200	.69	Full
1 5/8"	2 1/8"	5"	200	.75	Full
1 7/8"	2 3/8"	6"	200	.84	Full
2"	2 1/2"	6"	200	.88	Full
2 3/8"	2 7/8"	6"	150	1.26	Full
2 1/2"	3"	10"	150	1.33	Full
2 7/8"	3 1/16"	11"	125	1.62	Full
3"	3 9/16"	12"	125	1.68	Full
3 1/2"	4 1/16"	15"	125	1.94	Full
4"	4 5/8"	18"	125	2.51	Full
4 1/2"	5 1/8"	24"	100	2.78	Full
5"	5 5/8"	30"	100	3.04	Full
5 9/16"	6 3/16"	34"	100	3.38	Full
6"	6 5/8"	36"	100	3.79	Full
6 5/8"	7 1/4"	40"	100	4.25	Full

SW469 HARDWALL MARINE FUEL FILL HOSE

Meets U.S.C.G. Standards for specification SAE J1527 TYPE B2.



- Flexible, hardwall marine hose for use in fuel fill and vent applications on marine fuel systems.
- Specifically designed to handle high temperatures.

Tube: Extruded Nitrile.
Reinforcement: Textile with dual wire helix.
Cover: Specially compounded Nitrile.
Temperature: -40° to +200°F.

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1/2"	7/8"	4"	50	.24	Full
5/8"	1"	4"	50	.28	Full
3/4"	1 1/8"	4"	50	.32	Full
7/8"	1 1/4"	4"	50	.36	Full
1"	1 3/8"	4"	50	.39	Full
1 1/8"	1 1/2"	4"	50	.44	Full
1 1/4"	1 5/8"	4"	50	.47	Full
1 5/16"	1 11/16"	4"	50	.49	Full
1 3/8"	1 3/4"	4"	50	.52	Full
1 1/2"	1 7/8"	4"	50	.56	Full
1 5/8"	2"	6"	50	.59	Full
1 3/4"	2 1/8"	6"	50	.63	Full
1 7/8"	2 1/4"	6"	50	.71	Full
2"	2 3/8"	6"	50	.78	Full
2 1/8"	2 1/2"	6"	50	.84	Full
2 1/4"	2 5/8"	6"	50	.91	Full
2 3/8"	2 3/4"	6"	50	.95	Full
2 1/2"	2 7/8"	10"	50	1.00	Full
2 5/8"	3"	10"	40	1.08	Full
2 3/4"	3 1/8"	10"	40	1.15	Full
2 7/8"	3 1/4"	10"	35	1.25	Full