

## SW387 HOT TAR & ASPHALT HOSE - NITRILE TUBE

**Caution:** Do not use for continuous service or above 350° F.  
Refer to SW327 (page 58) for continuous service applications.



- High temperature hose designed for hot tar, hot oil and unrefined petroleum products.
- Premium grade tube handles high temperatures up to 350°F. at intermittent service.
- Dual helix wire provides full vacuum capabilities.
- Specially formulated cover is heat and ozone resistant.

**Tube:** Extruded heat resistant Nitrile.  
**Reinforcement:** Textile with dual wire helix.  
**Cover:** Nitrile.  
**Temperature:** -40° to +350°F. (Intermittent service only).

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1 1/2"	2 1/8"	6"	150	.95	Full
2"	2 5/8"	8"	150	1.39	Full
2 1/2"	3 3/8"	10"	150	1.82	Full
3"	3 3/4"	12"	150	2.38	Full
4"	4 13/16"	18"	150	3.66	Full

## SWC316 PETROMAX PETROLEUM SUCTION - BLACK COVER

- Extremely flexible petroleum suction & discharge hose designed for tank truck service.
- Deep corrugated construction provides extreme flexibility and a tight bend radius without kinking or crushing.
- High grade cover is ozone, abrasion and oil resistant.

**Tube:** Extruded Nitrile.  
**Reinforcement:** Textile with dual wire helix.  
**Cover:** Corrugated specially compounded Nitrile (Black or Red).  
**Temperature:** -40° to +180°F.



I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1"	1 9/16"	3"	150	.61	Full
1 1/2"	2 1/16"	4"	150	.85	Full
2"	2 9/16"	5"	150	1.18	Full
2 1/2"	3 1/16"	6"	150	1.39	Full
3"	3 19/32"	9"	150	1.84	Full
4"	4 19/32"	12"	150	2.60	Full
6"	6 3/4"	18"	125	4.79	Full

## SWC316R PETROMAX PETROLEUM SUCTION - RED COVER

I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1"	1 9/16"	3"	150	.61	Full
1 1/2"	2 1/16"	4"	150	.85	Full
2"	2 9/16"	5"	150	1.18	Full
2 1/2"	3 1/16"	6"	150	1.39	Full
3"	3 19/32"	9"	150	1.84	Full
4"	4 19/32"	12"	150	2.60	Full
6"	6 3/4"	18"	125	4.79	Full