

Fuel Injection Hose SAE 30R9



Application: Designed specifically for auto and truck fuel injection systems. Goodyear Engineered Products SAE 30R9 is CARB approved (C-U-06-011) with a maximum fuel permeation of 15 g/m²/day at 40°C.

Specific Fuel: Gasoline, ethanol extended gasoline, oxidized sour gas, diesel fuel, biodiesel, lubrication oil

Construction

Tube: Blue Fluoroelastomer/Nitrile

Reinforcement: Aramid Spiral

Cover: Black Hypalon* (CSM)



Temperature Range F & C: -29° to +275°F (-34° to +135°C) Intermittent use at +302°F (+150°C)

SAE Specifications: SAE J30R9

USCG Specifications: NA

Goodyear Engineered Products Specification: 599965

Length: See table below. 1.5' (clamshell), 25' (spool)

Brand Layline: Goodyear (size in inches) Fuel Injection Hose SAE J30R9 (date code) (country code) (time of manufacture)

Installation: See selection of Goodyear EP clamps

Warning: Do not submerge in gasoline

Part Number	ID(in.)	OD(in.)	Length(ft.)	Working Pressure(PSI)	Burst Pressure(PSI)	Min Bend Radius(in.)	Vacuum HG(in.)	Weight (lbs./ft.)
65148	1/4	.50	1.5	max 100	900	0.75	24	0.10
65151	1/4	.50	25	max 100	900	0.75	24	0.10
65149	5/16	.56	1.5	max 100	900	0.84	24	0.12
65152	5/16	.56	25	max 100	900	0.84	24	0.12
65150	3/8	.63	1.5	max 100	900	0.94	24	0.14
65153	3/8	.63	25	max 100	900	0.94	24	0.14
65164	1/2	.80	25	max 100	900	2.00	24	0.16



For clamps see page 47.

*Hypalon is registered by DuPont Dow Elastomers, LLC.