



# Flexline Hose Product Guide

## Contents

- 3 PROTECTASHIELD Hose Coating
- 4 Municipal Fire and Forestry Hose
- 6 Industrial Fire and General Purpose Hose
- 8 Couplings

### FLEXLINE HOSE, THE PROFESSIONALS CHOICE

Flexline, part of the Kidde Fire Fighting organization, is a quality brand of woven jacket and rubber fire and industrial hose and hose products. Products manufactured from high quality raw materials to exacting standards make Flexline hose a durable and reliable performer, offering a complete range of products for general purpose use, industrial, municipal and forestry fire fighting.



MUNICIPAL



INDUSTRIAL



FORESTRY

# PROTECTASHIELD™ Hose Coating

## Performance you can count on

All Flexline woven jacket products are available with our new, unique, innovative abrasion resistant coating. PROTECTASHIELD completely encapsulates the fibers of our jacket, providing a long lasting, vibrant color shield against the rough treatment that fire hose is exposed to every day. PROTECTASHIELD displays extreme resistance to bacterial and mildew growth as well.

When subjected to the Mil-H-24606B Taber Abrader test, PROTECTASHIELD surpassed the minimum requirement by 6 times compared to other hose manufacturers. This coating is available on Flexline AP8D, AP8DTP, Flexatak, Flexlite, AP6D, AP6, AP5, AP3, and FTP6 hose products.

PROTECTASHIELD is offered in six vibrant NFPA recommended colors; red, yellow, orange, blue, green and tan.

Specify

PROTECTASHIELD to  
ensure that you get the  
very best abrasion  
resistant protection.



# Municipal Fire and Forestry Hose

## AP8D

### Polyester Double Jacket Rubber Lined Fire Hose

Flexline AP8D												
Size inch mm	Service		Pressure Proof		Burst		Bowl Size		Weight* 50' (15m)		Coil Diameter 50' (15m)	
	psi	kPa	psi	kPa	psi	kPa	inch	mm	lbs.	kg	inch	mm
1-1/2 38	400	2800	800	5600	1200	8400	1-15/16	49	15	6.8	18	457
1-3/4 45	400	2800	800	5600	1200	8400	2-1/8	54	22	9.9	18	457
2-1/2 65	400	2800	800	5600	1200	8400	3	76	31	14.0	21	533
3 75	400	2800	800	5600	1200	8400	3-9/16	90	42	18.9	21	533

Flexline AP8D is the ultimate in quality, municipal grade fire hose. This durable, double jacket hose is constructed of 100% high tensile strength polyester yarns, both warp and filler, and lined with a high-tech E.P.D.M. tube. Its engineered design guarantees minimum weight with maximum durability and flexibility. The standard color for AP8D Hose is white. Other colors available with our innovative PROTECTASHIELD abrasion resistant coatings are red, yellow, orange, blue, green and tan.

## AP8DTP

### Polyester Double Jacket Urethane Lined Fire Hose

Flexline AP8DTP												
Size inch mm	Service		Pressure Proof		Burst		Bowl Size		Weight* 50' (15m)		Coil Diameter 50' (15m)	
	psi	kPa	psi	kPa	psi	kPa	inch	mm	lbs.	kg	inch	mm
1-1/2 38	400	2800	800	5600	1200	8400	1-15/16	49	12	5.4	16	406
1-3/4 45	400	2800	800	5600	1200	8400	2-1/8	54	14	6.3	16	406
2-1/2 65	400	2800	800	5600	1200	8400	3	76	25	11.3	19	483
3 75	400	2800	800	5600	1200	8400	3-9/16	90	31	14.0	19	483

Flexline AP8DTP is a lightweight hose that utilizes a thin, high tensile thermoplastic lining to minimize weight. Both the inner and outer jackets are constructed of polyester warp yarns and filament polyester filler yarns. AP8DTP's lining meets the NSF (National Sanitation Foundation) Standard 61 for potable water and has a tensile strength of over 5000 psi (35,000 kPa). AP8DTP is U.L. Listed. The standard color for AP8DTP Hose is white. Other colors available with our innovative PROTECTASHIELD abrasion resistant coatings are red, yellow, orange, blue, green and tan.

## Flexatak

### Nylon Double Jacket Rubber Lined Fire Hose

Flexline Flexatak												
Size inch mm	Service		Pressure Proof		Burst		Bowl Size		Weight* 50' (15m)		Coil Diameter 50' (15m)	
	psi	kPa	psi	kPa	psi	kPa	inch	mm	lbs.	kg	inch	mm
1-1/2 38	400	2800	800	5600	1200	8400	1-15/16	49	14	6.3	18	457
1-3/4 45	400	2800	800	5600	1200	8400	2-1/8	54	18	8.1	18	457
2-1/2 65	400	2800	800	5600	1200	8400	3	76	25	11.3	20	508
3 75	400	2800	800	5600	1200	8400	3-9/16	90	35	15.8	21	533
4 100	300	2100	600	4200	900	6300	4-17/32	115	41	18.6	25	635
5 125	300	2100	600	4200	900	6300	5-15/32	139	58	26.3	27	686

Flexline Flexatak is constructed of high strength, low stretch entangled filament polyamide/cordura fibers over a rubber, ozone proof, E.P.D.M. tube. Flexatak Hose is available with our innovative PROTECTASHIELD abrasion resistant coating. The standard colors are red, yellow, orange, blue, green and tan.

## Flexlite

### Nylon Double Jacket Urethane Lined Fire Hose

Flexline Flexlite												
Size inch mm	Service		Pressure Proof		Burst		Bowl Size		Weight* 50' (15m)		Coil Diameter 50' (15m)	
	psi	kPa	psi	kPa	psi	kPa	inch	mm	lbs.	kg	inch	mm
1-1/2 38	400	2800	800	5600	1200	8400	1-15/16	49	12	5.4	16	406
1-3/4 45	400	2800	800	5600	1200	8400	2-1/8	54	14	6.3	16	406
2-1/2 65	400	2800	800	5600	1200	8400	3	76	19	8.6	18	457
3 75	400	2800	800	5600	1200	8400	3-9/16	90	28	12.6	19	483
4 100	300	2100	600	4200	900	6300	4-17/32	105	35	15.8	20	508

Flexline Flexlite utilizes high strength, low stretch entangled filament polyamide/cordura fibers to produce a highly abrasion-resistant lightweight hose. The high-tech thermoplastic lining also contributes to reducing the overall weight of the hose. Flexlite's lining has a tensile strength of over 5000 psi (35,000 kPa). Flexlite Hose is available with our innovative PROTECTASHIELD abrasion resistant coating. The standard colors are red, yellow, orange, blue, green and tan.

## TM8 Taskmaster

### 100% All Synthetic Woven Jacket with Nitrile Inner Tube Double Jacket

Flexline TM8 Taskmaster												
Size inch mm	Service		Pressure Proof		Burst		Bowl Size		Weight* 50' (15m)		Coil Diameter 50' (15m)	
	psi	kPa	psi	kPa	psi	kPa	inch	mm	lbs.	kg	inch	mm
1-3/4 45	400	2800	800	5600	1200	8400	2-1/8	54	18	8.1	16.5	419
2-1/2 65	400	2800	800	5600	1200	8400	3	76	23	10.4	18.5	470

This all synthetic fire hose is designed for municipal fire protection. The outer jacket is made from a high quality HiVis Yellow polyester filament with white I.D. stripe. The inner jacket/lining is a one piece extruded through-the-weave nitrile rubber tube which provides high GPM flow with low friction loss. The finished design couples high abrasion resistance and durability with low overall weight and low drag.



## Flowmaster Attack Lightweight Attack Hose

Flexline Flowmaster Attack											
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*	Coil Diameter
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m) lbs. kg	50' (15m) inch mm
1	25	300	2100	600	4200	900	6300	1-1/4	32	8 3.6	15 381
1-1/2	38	300	2100	600	4200	900	6300	1-13/16	46	16 7.3	16 406
1-3/4	45	300	2100	600	4200	900	6300	2-1/16	52	18 8.2	16 406
2	50	300	2100	600	4200	900	6300	2-5/16	59	20 9.1	17 432
2-1/2	65	300	2100	600	4200	900	6300	2-7/8	73	27 12.2	18 457

Flexline Flowmaster Attack is a lightweight nitrile rubber through-the-weave construction fire hose. Its synthetic jacket is completely protected and locked in by a rubber cover and lining for extra toughness and durability. A heavy rib construction makes this hose resistant to cuts, punctures, impact and abrasion. Flowmaster Attack is a 600 psi (4200 kPa) fire hose that withstands temperatures from 1200°F to -37°F, (649°C to -38°C). Its light-weight design is virtually non-kinking and ideal for municipal fire protection. The standard colors for Flowmaster Attack are yellow and red, 1" size is available in yellow only.

## Flowmaster Supply Large Diameter Supply Hose

Flexline Flowmaster Supply											
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*	Coil Diameter
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	100' (30m) lbs. kg	100' (30m) inch mm
3	75	300	2100	600	4200	900	6300	3-13/32	87	70 31.5	25 635
4	100	225	1575	450	3150	675	4725	4-5/16	110	90 40.5	24 610
5	125	200	1400	400	2800	600	4200	5-3/8	137	109 49.1	27 686

Flexline Flowmaster Supply is a tough large diameter hose with the ability to deliver more water at a lower cost. But it doesn't stop there. It is lightweight, compact and durable with a high resistance to oils, chemicals, ozone and heat. Its tough, high tensile cover and lining, permanently interlocked with the synthetic reinforcement, provide greater abrasion resistance while being snag-proof, kink resistant, and immune to mildew or rot. U.L. labeling is available on 4" (100 mm) and 5" (125 mm) only. The standard colors for Flowmaster Supply are yellow or red.

## Flexline FLEX6 Rubber Covered Through-The-Weave Forestry Hose

Flexline FLEX6											
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*	Coil Diameter
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	100' (30m) lbs. kg	100' (30m) inch mm
1	25	300	2100	600	4200	900	6300	1-1/4	31.8	10 4.5	16 406
1-1/2	38	300	2100	600	4200	900	6300	1-11/16	42.9	17 7.5	18 457

Nitrile rubber covered forestry hoses that require no washing or drying and are mildew resistant. A protective rubber covering resists burns and prevents damage of the textile reinforcement which may be caused by abrasion or hot embers. The standard color is high visibility yellow. There is a minimum order quantity for 1-1/2" size.

## Flexline FTP6 Polyester Single Jacket Plastic Lined Forestry Hose

Flexline FTP6											
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*	Coil Diameter
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m) lbs. kg	50' (15m) inch mm
1	25	300	2100	600	4200	900	6300	1-1/4	31.8	7.5 3.4	14 356
1-1/2	38	300	2100	600	4200	900	6300	1-3/4	45	13.5 6.1	16 406

A lightweight polyester jacket, polyurethane lined forestry fire hose that meets the USDA-US Forest Service Specification 5100-187. The standard color for Flexline FTP6 is white. Other colors available are yellow.

\* Weight is uncoupled

# Industrial Fire and General Purpose Hose

## Flexline AP6D Polyester Double Jacket Rubber Lined Fire Hose

Flexline AP6D											
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*	Coil Diameter
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m) lbs. kg	50' (15m) inch mm
1-1/2	38	300	2100	600	4200	900	6300	1-15/16	49	15 6.8	18 457
1-3/4	45	300	2100	600	4200	900	6300	2-1/8	54	22 9.9	18 457
2-1/2	65	300	2100	600	4200	900	6300	3	76	31 14.0	21 533
3	75	300	2100	600	4200	900	6300	3-9/16	90	38 17.1	21 533

This heavy duty double jacket industrial fire hose is designed for daily use where higher pressure and additional abrasion resistance is required. Construction of 100% high tensile strength virgin polyester yarns, both warp and filler, provides extra durability. Hose comes standard with E.P.D.M. lining. U.L. labeling is available in 1-1/2", 1-3/4", and 2-1/2" sizes. The standard color for Flexline AP6D Hose is white. Other colors available with our innovative PROTECTASHIELD abrasion resistant coatings are red, yellow, orange, blue, green and tan.

## Flexline AP6S Polyester Single Jacket Rubber Lined Fire Hose

Flexline AP6S											
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*	Coil Diameter
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m) lbs. kg	50' (15m) inch mm
1-1/2	38	300	2100	600	4200	900	6300	1-13/16	46	11 5.0	15 381
2-1/2	65	300	2100	600	4200	900	6300	2-7/8	73	22 9.9	16 406

A single jacket, polyester industrial fire hose with an ozone-resistant E.P.D.M. rubber lining. The spun polyester yarn in the jacket offers superior strength and wear characteristics. Designed for interior or exterior fire protection, Flexline AP6S is NFPA compliant as an attack hose. The polyester construction is mildew resistant. The standard color for Flexline AP6S Hose is white. Other colors available with our innovative PROTECTASHIELD abrasion resistant coatings are red, yellow, orange, blue, green and tan.

## Flexline AP5 Polyester Single Jacket Rubber Lined Fire Hose

Flexline AP5											
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*	Coil Diameter
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m) lbs. kg	50' (15m) inch mm
1-1/2	38	250	1750	500	3500	750	5250	1-13/16	46	11 5.0	15 381
2-1/2	65	250	1750	500	3500	750	5250	2-7/8	73	22 9.9	16 406

A single jacket, polyester industrial fire hose with an ozone-resistant E.P.D.M. rubber lining. The spun polyester yarn in the jacket offers superior strength and wear characteristics. The polyester construction is mildew resistant. U.L. labeling is available in 1-1/2" and 2-1/2" sizes. The standard color for Flexline AP5 Hose is white. Other colors available with our innovative PROTECTASHIELD abrasion resistant coatings are red, yellow, orange, blue, green and tan.

## Flexline AP3 Polyester Single Jacket Rubber Lined Fire Hose

Flexline AP3											
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*	Coil Diameter
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m) lbs. kg	50' (15m) inch mm
1-1/2	38	150	1050	300	2100	450	3150	1-13/16	46	11 5.0	15 381
2-1/2	65	150	1050	300	2100	450	3150	2-7/8	73	22 9.9	16 406

A single jacket, polyester industrial fire hose with an ozone-resistant E.P.D.M. rubber lining. The spun polyester yarn in the jacket offers superior strength and wear characteristics. The polyester construction is mildew resistant. U.L. labeling is available in 1-1/2" and 2-1/2" sizes. The standard color for Flexline AP3 Hose is white. Other colors available with our innovative PROTECTASHIELD abrasion resistant coatings are red, yellow, orange, blue, green and tan.

## Flexline RR5 Polyester Single Jacket Rack and Reel Hose

Flexline RR5											
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*	Coil Diameter
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m) lbs. kg	50' (15m) inch mm
1-1/2	38	250	1750	500	3500	750	5250	1-11/16	43	5 2.3	12 305
2-1/2	65	250	1750	500	3500	750	5250	2-11/16	68	13 5.9	17 432

This interior fire protection hose is designed to replace unlined linen length for length. This polyester, urethane lined hose is ideal for interior rack or reel service. Flexline RR5 is available folded for standard pin racks in 50' (15m), 75' (22.5m), and 100' (30m) lengths. Specify folded, coiled, or number of pins for rack (15 pins for 50', 20 pins for 75', or 25 pins for 100'). The standard color for Flexline RR5 is white. U.L. label and (or) FM approval is available on 1-1/2" size.

**Flexline EXN5**  
Through-The-Weave Industrial Fire Hose

Flexline EXN5													
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*	Coil Diameter		
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m)	50' (15m)		
										lbs.	kg		
										inch	mm		
1-1/2	38	250	1750	500	3500	750	5250	1-3/4	44	10	4.5	12	305
1-3/4	45	250	1750	500	3500	750	5250	2	51	14	6.3	14	356
2	50	250	1750	500	3500	750	5250	2-3/16	56	18	8.1	14	356
2-1/2	65	250	1750	500	3500	750	5250	2-3/4	70	19	8.6	14	356

Flexline EXN5 is a layflat, lightweight, flexible fire hose specifically designed for industrial fire protection. EXN5 is U.L. approved and features a unique through-the-weave, one piece construction that will not delaminate. The synthetic reinforcement is totally encased in a PVC nitrile rubber cover and lining which is resistant to fuels, oils, chemicals, abrasion, heat, mildew, rot, and ozone. The colors available for Flexline EXN5 are red and yellow.

**Flexline EXN4**  
Large Diameter Supply Hose

Flexline EXN4													
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*	Coil Diameter		
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m)	50' (15m)		
										lbs.	kg		
										inch	mm		
4	100	200	1400	400	2800	600	4200	4-5/16	110	42	19.0	18.0	457
5	125	200	1400	400	2800	600	4200	5-3/8	137	57	25.7	19	483
6	150	200	1400	400	2800	600	4200	6-15/32	164	78	35.1	20.0	508

The through-the-weave design allows the hose to expand under pressure which decreases friction loss and increases water flow. The ozone resistant synthetic rubber liner and cover totally encompass and protect the synthetic reinforcement from the effects of abrasion, chemicals and heat. These products are easily cleaned and are ideally suited for fire fighting and other demanding industrial applications. Colors available are red and yellow.

**Flexline M250**  
Single Jacket Polyester Mill Hose

Flexline M250													
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*	Coil Diameter		
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m)	50' (15m)		
										lbs.	kg		
										inch	mm		
1	25	125	875	250	1750	500	3500	1-1/4	32	8	3.6	13	330
1-1/2	38	125	875	250	1750	500	3500	1-11/16	43	10	4.5	14	356
2	50	125	875	250	1750	500	3500	2-3/8	60	16	7.2	15	381
2-1/2	65	125	875	250	1750	500	3500	2-11/16	68	20	9.0	15	381
3	75	125	875	250	1750	500	3500	3-3/8	86	27	12.2	17	432

A heavy duty industrial, constructed of 100% spun polyester for abrasive environments and low maintenance. Designed for water discharge and other low pressure applications such as washdown. The liner is SBR for petrochemical resistance. The standard color for Flexline M250 is white.

**Flexline EXN4**  
Lightweight Through-The-Weave Washdown Hose

Flexline EXN4													
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*	Coil Diameter		
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m)	50' (15m)		
										lbs.	kg		
										inch	mm		
1-1/2	38	225	1575	450	3150	750	5250	1-3/4	44	10	4.5	12	305
2	50	225	1575	450	3150	750	5250	2-3/16	56	15	6.8	13	330
2-1/2	65	225	1575	450	3150	750	5250	2-3/4	70	19	8.6	14	356

Flexline EXN4 is a layflat, lightweight, flexible maintenance hose with the durability and abrasion resistance of heavy duty rubber hose. EXN4 features a unique through-the-weave, one piece construction that will not delaminate. The synthetic reinforcement is totally encased in nitrile rubber cover and lining which is resistant to fuels, chemicals, and oil. EXN4 will not mildew or rot and is heat and ozone resistant. The standard color for EXN4 is blue.

**Flexline EXN6**  
Heavy Duty Rubber Covered Industrial Discharge Hose

Flexline EXN6													
Size		Service		Pressure Proof		Burst		Bowl Size		Weight*	Coil Diameter		
inch	mm	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m)	50' (15m)		
										lbs.	kg		
										inch	mm		
1-1/2	38	300	2100	600	4200	900	6300	1-13/16	45	16	7.2	15	381
1-3/4	45	300	2100	600	4200	900	6300	2-1/16	52	19	8.6	16	406
2	50	300	2100	600	4200	900	6300	2-3/16	56	20	9.0	16	406
2-1/2	65	300	2100	600	4200	900	6300	2-7/8	73	25	11.3	17	432
3	75	300	2100	600	4200	900	6300	3-13/32	87	35	15.8	18	457

Flexline EXN6 is a layflat, flexible water discharge hose with durability and abrasion resistance superior to conventional rubber hose. Flexline EXN6 features a unique one piece, through-the-weave construction, and attains its exceptional working pressure from a synthetic woven textile. Its excellent durability is derived from a high-tensile rubber compound which completely encases the jacket. The standard colors for Flexline EXN6 are yellow and red.

# COUPLINGS



The chart below indicates standard couplings offered for each type and size of Flexline hose products. Please consult your dealer for other available coupling options.

Hose Type Size	NH			NPSH			Storz Expansion Ring	Storz Clamp
	RL Aluminum	RL Brass	PL Brass	RL Aluminum	RL Brass	PL Brass		
<b>FTP6</b>								
1"				X				
1-1/2"	X			X				
<b>RR5 and M250</b>								
1"	X			X				
1-1/2"	X	X	X	X	X	X		
2"	X			X	X			
2-1/2"	X	X	X	X	X	X		
3"	X			X				
<b>AP6S, AP5, and AP3</b>								
1-1/2"	X	X	X	X	X	X		
2-1/2"	X	X	X	X	X	X		
<b>AP8D, AP8DTP, Flexatak, Flexlite, and AP6D</b>								
1-1/2"	X	X	X	X	X	X		
1-3/4"	X			X				
2-1/2"	X	X	X	X	X			
3"	X			X				
4"	X							X
5"	X							X
<b>EXN5 and EXN4</b>								
1-1/2"	X	X	X	X	X	X		
1-3/4"	X			X				
2"	X							
2-1/2"	X	X		X				
3"	X			X				
<b>Flowmaster Attack, FLEX6, and EXN6</b>								
1"	X			X				
1-1/2"	X	X	X	X	X	X		
1-3/4"	X		X	X				
2"	X	X		X	X			
2-1/2"	X	X	X	X	X	X		
3"	X			X				
<b>Flowmaster Supply</b>								
3"	X						X	X
4"	X							X
5"	X						X	X
<b>Taskmaster</b>								
1-3/4"	X			X				
2-1/2"	X							

### Legend

NH = National Standard Thread

RL = Rocker Lug