

Industrial Woven and Rubber Fire Hose



Angus RR500 Polyester Single Jacket Rack and Reel Hose

This interior fire protection hose is designed to replace unlined linen length for length. This polyester, urethane lined hose is ideal for interior rack or reel service. Angus RR500 is available folded for standard pin racks in 50' (15m), 75' (22.5m), and 100' (30m) lengths. Specify folded, coiled, or number of pins for rack (15 pins for 50', 20 pins for 75', or 25 pins for 100'). The standard color for Angus RR500 is white. UL label and FM approval is available. UL / FM hose is rated at 150 PSI service pressure.

Angus RR500											
Size inch mm	Service		Pressure Proof		Burst		Bowl Size		Weight*		Coil Diameter
	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m) lbs. kg	50' (15m) inch mm	
1-1/2 38	250	1750	500	3500	750	5250	1-11/16	43	5	2.3	12 305

Redskin 500 Through-The-Weave Industrial Fire Hose


Angus Redskin 500 is a layflat, lightweight, flexible fire hose specifically designed for industrial fire protection. Redskin is U.L. approved and features a unique through-the-weave, one piece construction that will not delaminate. The synthetic reinforcement is totally encased in a PVC nitrile rubber cover and lining which is resistant to fuels, oils, chemicals, abrasion, heat, mildew, rot, and ozone. The standard colors for Redskin 500 are red and yellow.

Angus Redskin 500											
Size inch mm	Service		Pressure Proof		Burst		Bowl Size		Weight*		Coil Diameter
	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m) lbs. kg	50' (15m) inch mm	
1-1/2 38	250	1750	500	3500	750	5250	1-3/4	44	10	4.5	12 305
1-3/4 45	250	1750	500	3500	750	5250	2	51	14	6.3	14 356
2-1/2 65	250	1750	500	3500	750	5250	2-3/4	70	19	8.6	14 356
3 75	250	1750	500	3500	750	5250	3-13/32	87	35	15.8	18 457

Redskin 600 Through-The-Weave Industrial Fire Hose

Angus Redskin 600 is a layflat, lightweight, flexible fire hose specifically designed for industrial fire protection. Redskin is U.L. approved and features a unique through-the-weave, one piece construction that will not delaminate. The synthetic reinforcement is totally encased in a PVC nitrile rubber cover and lining which is resistant to fuels, oils, chemicals, abrasion, heat, mildew, rot, and ozone. The standard colors for Redskin 600 are red and yellow.

Angus Redskin 600											
Size inch mm	Service		Pressure Proof		Burst		Bowl Size		Weight*		Coil Diameter
	psi	kPa	psi	kPa	psi	kPa	inch	mm	50' (15m) lbs. kg	50' (15m) inch mm	
1-1/2 38	300	2100	600	4200	900	6300	1-3/4	44	10	4.5	12 305
1-3/4 45	300	2100	600	4200	900	6300	2	51	14	6.3	14 356
2-1/2 65	300	2100	600	4200	900	6300	2-3/4	70	19	8.6	14 356
3 75	300	2100	600	4200	900	6300	3-13/32	87	35	15.8	18 457

 Factory Mutual Approved
* Weight is uncoupled