

Industrial General Purpose Hose



Angus M250 Single Jacket Polyester Mill Hose

A heavy duty industrial mill hose, constructed of 100% spun polyester for abrasive environments and low maintenance. Designed for water discharge and other low pressure applications such as washdown. The liner is SBR for petrochemical resistance. The standard color for Angus M250 is white.

Angus M250											
Size inch mm	Service psi kPa	Pressure Proof		Burst		Bowl Size		Weight* 50' (15m)		Coil Diameter 50' (15m)	
		psi	kPa	psi	kPa	inch	mm	lbs.	kg	inch	mm
1 25	125 875	250	1750	500	3500	1-1/4	32	8	3.6	13	330
1-1/2 38	125 875	250	1750	500	3500	1-11/16	43	10	4.5	14	356
2 50	125 875	250	1750	500	3500	2-3/8	60	16	7.2	15	381
2-1/2 65	125 875	250	1750	500	3500	2-11/16	68	20	9.0	15	381
3 75	125 875	250	1750	500	3500	3-3/8	86	27	12.2	17	432

Blue Skin Lightweight Through-The-Weave Washdown Hose

Angus Blue Skin is a layflat, lightweight, flexible maintenance hose with the durability and abrasion resistance of heavy duty rubber hose. Blue Skin features a unique through-the-weave, one piece construction that will not delaminate. The synthetic reinforcement is totally encased in nitrile rubber cover and lining which is resistant to fuels, chemicals, and oil. Blue Skin will not mildew or rot and is heat and ozone resistant. The standard color for Blue Skin is blue.

Angus Blue Skin											
Size inch mm	Service psi kPa	Pressure Proof		Burst		Bowl Size		Weight* 50' (15m)		Coil Diameter 50' (15m)	
		psi	kPa	psi	kPa	inch	mm	lbs.	kg	inch	mm
1-1/2 38	225 1575	450	3150	750	5250	1-3/4	44	10	4.5	12	305
2 50	225 1575	450	3150	750	5250	2-3/16	56	15	6.8	13	330
2-1/2 65	225 1575	450	3150	750	5250	2-3/4	70	19	8.6	14	356

Armour Guard Heavy Duty Rubber Covered Industrial Discharge Hose

Angus Armour Guard is a layflat, flexible water discharge hose with durability and abrasion resistance superior to conventional rubber hose. Armour Guard features a unique one piece, through-the-weave construction, and attains its exceptional working pressure from a synthetic woven textile. Its excellent durability is derived from a high-tensile rubber compound which completely encases the jacket. The standard color for Armour Guard is black.

Angus Armour Guard											
Size inch mm	Service psi kPa	Pressure Proof		Burst		Bowl Size		Weight* 50' (15m)		Coil Diameter 50' (15m)	
		psi	kPa	psi	kPa	inch	mm	lbs.	kg	inch	mm
1-1/2 38	300 2100	600	4200	900	6300	1-13/16	45	16	7.2	15	381
2 50	300 2100	600	4200	900	6300	2-3/16	56	20	9.0	16	406
2-1/2 65	300 2100	600	4200	900	6300	2-7/8	73	25	11.3	17	432
3 75	300 2100	600	4200	900	6300	3-13/32	87	35	15.8	18	457
4 100	200 1400	400	2800	600	4200	4-5/16	110	40	18.0	19	483
6 150	200 1400	400	2800	600	4200	6-3/8	162	80	36.0	21	533

* Weight is uncoupled