

Wildland & Forestry Fire Hose



Angus Super Inch / Super Marshall Rubber Covered Through-The-Weave Fire Hose

Nitrile rubber covered forestry hoses that require no washing or drying and are mildew resistant. A protective rubber covering resists burns and prevents damage of the textile reinforcement which may be caused by abrasion or hot embers. The standard color is high visibility yellow. There is a minimum order quantity for 1-1/2" size.

Size inch mm	Service		Pressure Proof		Burst		Bowl Size		Weight* 100' (30m)		Coil Diameter 100' (30m)	
	psi	kPa	psi	kPa	psi	kPa	inch	mm	lbs.	kg	inch	mm
1 25	300	2100	600	4200	900	6300	1-1/4	31.8	10	4.5	16	406
1-1/2 38	300	2100	600	4200	900	6300	1-11/16	42.9	17	7.5	18	457

Angus AF187 Polyester Single Jacket Plastic Lined Fire Hose

A lightweight polyester jacket, polyurethane lined forestry fire hose that meets the USDA-US Forest Service Specification 5100-187. The standard color for Angus AF187 is white.

Size inch mm	Service		Pressure Proof		Burst		Bowl Size		Weight* 100' (30m)		Coil Diameter 100' (30m)	
	psi	kPa	psi	kPa	psi	kPa	inch	mm	lbs.	kg	inch	mm
1 25	300	2100	600	4200	900	6300	1-1/4	31.8	7.5	3.4	14	356
1-1/2 38	300	2100	600	4200	900	6300	1-3/4	45	13.5	6.1	16	406

Flexible Pipeline



Super Aquaduct Lay Flat Large Diameter

A specialized polyurethane hose, extruded through the weave cover and lining, reinforced with circular woven high tenacity polyester. Super Aquaduct is the only product of its kind which is NSF 61 certified for potable water. Designed for a variety of above ground high flow potable or fire water contingencies. Also available are many equipment options for fast and easy deployment and retrieval of this versatile hose product. Available in blue and orange.

Size inch mm	Max Working Pressure**		Burst Pressure		Weight* per foot	
	psi	kPa	psi	kPa	lbs.	kg
6 152	300	2100	600	4200	1.09	0.5
8 203	220	1540	500	3500	1.9	0.9
10 254	175	1225	400	2800	2.2	1
12 305	175	1225	400	2800	3.5	1.6

WAT-HOG Plastic Lined Industrial Hose

Angus WAT-HOG is a premium lay-flat, flexible hose designed to handle wastewater, sewer, treated, and reclaimed water. It combines the features of PVC hose with the durability and abrasion resistance of heavy rubber hose. WAT-HOG features a through the weave construction combining a woven textile with a polyurethane cover and liner that will not delaminate. This hose is approved for military fuel transfer, is resistant to fuels, chemicals, heat, weather and UV light. Available in orange and tan.

Size inch mm	Max Working Pressure**		Angus WAT-HOG Burst Pressure		Weight* per foot		Coil Diameter 50' (15m)	
	psi	kPa	psi	kPa	lbs.	kg	inch	mm
1-1/2 38	300	2100	600	4200	0.16	0.07	13.5	343
2-1/2 65	300	2100	600	4200	0.3	0.14	14	356
3 76	300	2100	600	4200	0.37	0.17	15	381
4 102	300	2100	600	4200	0.56	0.25	19.5	495
6 152	300	2100	600	4200	1.22	0.55	21	533

* Weight is uncoupled

** Or maximum working pressure of attached coupling, whichever is lower