

Couplings



The chart below indicates standard couplings offered for each type and size of Angus hose products. Please consult your dealer for other available coupling options.

Hose Type Size	NH			NPSH			Storz Expansion Ring	Storz Clamp
	RL Aluminum	RL Brass	PL Brass	RL Aluminum	RL Brass	PL Brass		
AF187								
1"				X				
1-1/2"	X			X				
RR500 and M250								
1"	X			X				
1-1/2"	X	X	X	X	X	X		
2"	X			X	X			
2-1/2"	X	X	X	X	X	X		
3"	X			X				
S600, S500, and S300								
1-1/2"	X	X	X	X	X	X		
2-1/2"	X	X	X	X	X	X		
Ultima, Ultima Lite, Premier, Firepower II, and D700								
1-1/2"	X	X	X	X	X	X		
1-3/4"	X			X				
2-1/2"	X	X	X	X	X			
3"	X			X				
4"	X							X
Red Skin 500, Red Skin 600, Blue Skin, and Hi-Power								
1-1/2"	X	X	X	X	X	X		
1-3/4"	X			X				
2"	X							
2-1/2"	X	X		X				
3"	X			X				
Red Chief, Yellow Chief, and Super Inch/Super Marshall								
1"	X			X				
1-1/2"	X	X	X	X	X	X		
1-3/4"	X		X	X				
2"	X	X		X	X			
2-1/2"	X	X	X	X	X	X		
3"	X			X				
Hi-Vol and Hi-Combat Lite								
3"	X						X	X
4"	X							X
5"	X						X	X
Hi-Combat II and Hi-Combat IIR								
1-3/4"	X			X				
2-1/2"	X							

Legend	
NH = National Standard Thread	RL = Rocker Lug
NPSH = National Straight Pipe Thread	PL = Pin Lug

Angus recommends annual hydrostatic service testing of all hoses in accordance with NFPA 1962 guidelines.