

Working Tension PIW	Temp Range	Minimum Pulley Dia	Weight PIW	Maximum Roll Width	FDA USDA	Flexco #	Clipper #	DESCRIPTION ABBREVIATION KEY
150#	-25°F to 225°F	4"	.075	72"		15, 125	2	
150#	-25°F to 225°F	6"	.085	72"		187, 25	3	BB = Bare Back
150#	-25°F to 225°F	6"	.105	72"		20, 125	2	
150#	-25°F to 225°F	8"	.138	84"		140, 187, 375, R2		Brush = Brushed Bottom
150#	-25°F to 225°F	10"	.154	72"		140, 375, R2		C = Conveyor
220#	-25°F to 225°F	10"	.145	72"		140, 187, 375, R2		CBS = Cover Both Sides
220#	0°F to 250°F	10"	.150	72"		140, 187, 375, R2		CD = Cold
220#	-25°F to 225°F	10"	.167	84"		140, 550, R5		CR = Cross Rigid
220#	-25°F to 225°F	12"	.195	84"		190, 550, R5		CT II = Chevron Top II
225#	-25°F to 225°F	8"	.122	72"		25, 187, R2	2	E = Elevator
330#	-25°F to 225°F	16"	.205	84"		190, 550, R5 1/2		FR = Fire Retardant
330#	-25°F to 225°F	16"	.215	84"		190, 550, R5 1/2		FS = Friction Surface
440#	-25°F to 225°F	18"	.220	90"		190, 550, R5 1/2		GR 2 = Grade 2 (SBR)
440#	-25°F to 225°F	20"	.280	84"		190, 550, R6		H = Hot
440#	-25°F to 225°F	20"	.295	60"		190, 550, R6		IMPG = Impregnated
600#	-25°F to 225°F	20"	.375	84"		1 1/2, R6		MOR = Moderate Oil Resistance
150#	0°F to 250°F	4"	.075	72"		125, 15	2	MRT = Mini Roughtop
220#	0°F to 250°F	12c, 14e	.095	72"		140, 187, 375, R5		MSHA = Mine Safety Health Act
330#	0°F to 250°F	16c, 18e	.130	72"		140, 550, R5		MSK = Mini Skim Coat
600#	0°F to 250°F	20c, 24e	.195	72"		140, 550, R5		OR = Oil Resistant
440#	0°F to 250°F	20"	.200	72"		190, 550, R5		ORS-HMB = Oil Resistant Hot Asphalt
220#	-25°F to 225°F	4"	.100	60"			3-4 1/2ht	Poly = Polyester
220#	-25°F to 225°F	4"	.090	60"			3-4 1/2ht	PU = Polyurethane
225#	-25°F to 225°F	4"	.135	60"			3-4 1/2ht, 4 1/2ht	PVC = Poly Vinyl Chloride
330#	-25°F to 225°F	4"	.125	60"			3-4 1/2ht, 4 1/2ht	RMV = Rubber Modified Vinyl
330#	-25°F to 225°F	4"	.123	60"			3-4 1/2ht, 4 1/2ht	RT = Roughtop
220#	0°F to 250°F	12"	.200	72"		190, 550, R5		SC = Static Conductive
330#	0°F to 250°F	16"	.220	72"		190, 550, R5		Tex = Texture
330#	0°F to 250°F	16"	.180	72"		190, 375, R5		
220#	0°F to 250°F	12"	.195	72"		190, 550, R5		
220#	-25°F to 400°F	12"	.195	48"		190, 550, R5		
220#	-25°F to 700°F	12"	.195	72"		190, 550, R5		
220#	0°F to 350°F	12"	.195	72"		190, 550, R5		
330#	0°F to 350°F	18"	.215	72"		190, 550, R5		
330#	-25°F to 400°F	18"	.232	72"		190, 550, R5 1/2		
330#	-25°F to 700°F	18"	.232	48"		190, 550, R5		
220#	-40°F to 225°F	12"	.130	60"		125, 20	2	
105#	-25°F to 225°F	4"	.130	72"		125, 7	1	
150#	-25°F to 225°F	4"	.120	72"		125, 7	1	
150#	-25°F to 225°F	4"	.120	72"		62, 7	25LP	
135#	-40°F to 250°F	4"	.100	72"		125, 20	2	
150#	0°F to 250°F	3 1/2"	.105	72"		62, 7	2	
135#	0°F to 250°F	4"	.130	72"		125, 20	2	
120#	20°F to 180°F	2 1/2"	.100	72"		125, 15	1	
150#	-40°F to 250°F	3 1/2"	.115	72"		125, 15	2	
150#	-20°F to 225°F	4"	.100	72"		125, 15	2	