

## Flx-Thane® LD



Size Range (In) . . . . . stock 2" to 18"  
Standard Length (Ft) . . . . . 25'  
Standard Colors . . . . . clear, black  
Temperature Range (°F) . . . . . -65° to 225°

- Light weight polyurethane hose reinforced with a bronze coated spring steel wire helix
- Great compressibility
- Great abrasion resistance
- Superior chemical resistance
- Excellent flexibility
- Designed for applications with wide temperature ranges
- Clear is manufactured with FDA acceptable materials
- Available in metric sizes, consult sales team on pricing & minimums
- Wall Thickness = .020"



## Flx-Thane® MD



Size Range (In) . . . . . stock 2" to 24"  
Standard Length (Ft) . . . . . 25', 50'  
Standard Colors . . . . . black, clear  
Temperature Range (°F) . . . . . -65° to 225°

- Medium weight polyurethane hose reinforced with a bronze coated spring steel wire helix
- Good compressibility
- Great abrasion resistance & high tear strength
- Superior chemical resistance
- Excellent flexibility
- Designed for applications with wide temperature ranges
- Very good low temperature flexibility
- Clear is manufactured with FDA acceptable materials
- Available in metric sizes, consult sales team on pricing & minimums
- Wall Thickness = .030"



## Flx-Thane® HD



Size Range (In) . . . . . stock 2" to 24"  
Standard Length (Ft) . . . . . 25'  
Standard Colors . . . . . clear, black  
(translucent blue available)  
Temperature Range (°F) . . . . . -65° to 225°

- Heavy weight polyurethane hose reinforced with a coated spring steel wire helix (sizes 14" I.D. & above not available with a coated wire)
- Great abrasion resistance & high tear strength
- Superior chemical resistance
- Excellent flexibility
- Designed for applications with wide temperature ranges
- Ideal for severe service applications
- Very good low temperature flexibility
- Clear is manufactured with FDA acceptable materials
- Available in metric sizes, consult sales team on pricing & minimums
- Wall Thickness = .045"



## Flx-Thane® VHD



Size Range (In) . . . . . stock 4" to 18"  
custom to 24"  
Standard Length (Ft) . . . . . 25'  
Standard Colors . . . . . clear, black  
(translucent blue available)  
Temperature Range (°F) . . . . . -65° to 225°

- Very heavy weight polyurethane hose reinforced with a coated spring steel wire helix (sizes 14" I.D. & above not available with a coated wire)
- Great abrasion resistance & high tear strength
- Superior chemical resistance
- Excellent flexibility
- Designed for applications with wide temperature ranges
- Ideal for severe service applications
- Very good low temperature flexibility
- Clear is manufactured with FDA acceptable materials
- Available in metric sizes, consult sales team on pricing & minimums
- Wall Thickness = .060"

