

## Flx-Thane® SD





- Great abrasion resistance & high tear strength
- Superior chemical resistance & excellent flexibility
- Designed for applications with wide temperature
- · Ideal for clean rooms and material plastic processing applications
- Reduces static build-up in material handling
- Surface resistance level: 108-1010 Ohms/Square
- Clear is manufactured with FDA acceptable materials
- Wall Thickness = .030"





## Flx-Thane® SE

		(),,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Size F	Range (In) .		stock 2" to 12" custom to 24"
Stand	ard Length	(Ft)	25', 50'
Standard Colorsclear			
Temperature Range (°F)65° to 225°			



- · Self-extinguishing medium weight polyurethane hose reinforced with a bronze coated spring steel wire helix
- Halogen-free
- Good compressibility
- Great abrasion resistance & high tear strength
- Superior chemical resistance
- **Excellent flexibility**
- · Designed for applications with wide temperature
- Good low temperature flexibility
- · Listed as UL 94V-0 flame retardant
- Wall Thickness = .030"



## **Flexadux® Accessories**

Also available for our Flexaust®, Heat-Flex™, Flex-Lok® (excluding Screw Clamps) & Springflex® hoses.



Reducers



Screw Clamps



Connectors





Pin-Locks

**Bridge Clamps** 

T's



J-Locks



Latch-Locks



**Branches**