

White



Size Range (In)stock 1½" to 24"
 Standard Length (Ft)25'
 Standard Colorswhite
 Temperature Range (°F)-20° to 325°

- Double-ply acrylic coated polyester fabric hose reinforced with a spring steel wire helix
- Efficient flow characteristics
- Designed for applications with wide temperature ranges
- Good abrasion resistance
- Ideal for clean room applications
- Manufactured with FDA acceptable materials



FSP-1



Size Range (In)stock 3" to 12"
 Standard Length (Ft)25'
 Standard Colorsblack with orange wearstrip
 Temperature Range (°F)-20° to 180°

- Single-ply PVC vinyl coated polyester fabric hose reinforced with a spring steel wire helix & external PVC wearstrip
- Wearstrip offers additional external abrasion & drag resistance
- Low friction loss
- Great chemical & moisture resistance
- Listed as UL 94V-0 flame retardant
- Other wearstrip colors available
- Available without a wearstrip for a more economical option
- Additional coatings available for better abrasion &/or chemical resistance
- Available in metric sizes, consult sales team on pricing & minimums



FSP-2



Size Range (In)stock 3" to 12"
 Standard Length (Ft)25'
 Standard Colorsblack with orange wearstrip
 Temperature Range (°F)-20° to 180°

- Double-ply PVC vinyl coated polyester fabric hose reinforced with a spring steel wire helix & external PVC wearstrip
- Wearstrip offers additional external abrasion & drag resistance
- Great moisture, mildew & chemical resistance
- Low friction loss
- Listed as UL 94V-0 flame retardant
- Other wearstrip colors available
- Available in a heavy duty bridge construction (FSP Bridge)
- Additional coatings available for better abrasion &/or chemical resistance



Flexaust® End Finishes

Also available for our Heat-Flex™ (excluding Reduced Cuff & Felt Flange) & Springflex® hoses.



Enlarged Cuff



Steel Flange



Fabric Cuff



Reduced Cuff



Felt Flange