Dust Material

Flex-Lok® SF







Size Range (In)	stock 3" to 18"
Standard Length (Ft)	25'
Standard Colors	silver
Temperature Range (°F)	65° to 550°





- · Single-ply silicone coated fiberglass fabric hose mechanically crimped in a continuous process
- Fabric is locked around a coated steel wire by a metal strip formed into a clip
- Metal strip acts as a wearstrip
- Outstanding resistance to external abrasion
- Extremely flexible
- · Ideal for vehicle exhaust applications with external abrasion
- Available with Hypalon® and neoprene coated materials (Flex-Lok® HP & Flex-Lok® NPB)
- Available with a polyurethane (PU-75 shore material) clip cover to protect the helix & the equipment that is attached to the hose



Flex-Lok® SF-2







Size Range (In) stock 3" to 1 custom to 1	
Standard Length (Ft) 2	5'
Standard Colors silv	er
Temperature Range (°F)65° to 750	n°



- · Double-ply silicone coated fiberglass fabric hose mechanically crimped in a continuous
- Fabric is locked around a coated steel wire by a metal strip formed into a clip
- Metal strip acts as a wearstrip
- Outstanding resistance to external abrasion
- Extremely flexible
- Ideal for high temperature fume control & vehicle exhaust applications with external abrasion
- Available with a polyurethane (PU-75 shore material) clip cover to protect the helix & the equipment that is attached to the hose



Flex-Lok® ET







Size Range (In) stock 3" to 12"
Standard Length (Ft)
Standard Colors silver
Temperature Range (°F)65° to 1050°
intermittent to 1250°



- · Single-ply aluminum coated fiberglass fabric hose mechanically crimped in a continuous process
- Fabric is locked around a coated steel wire by a metal strip formed into a clip
- Metal strip acts as a wearstrip
- Outstanding resistance to external abrasion
- Extremely flexible & compressible
- Ideal for vehicle exhaust applications
- Available with a polyurethane (PU-75 shore material) clip cover to protect the helix & the equipment that is attached to the hose
- Not recommended for continuous flexing



Flex-Lok® TF







- Size Range (In) stock 3" to 18" Standard Length (Ft) 25' Standard Colors silver Temperature Range (°F)....-65° to 500°
- · Single-ply Teflon® coated fiberglass fabric hose mechanically crimped in a continuous process
- Fabric is locked around a coated steel wire by a metal strip formed into a clip
- Metal strip acts as a wearstrip
- Outstanding resistance to external abrasion
- Extremely flexible
- Ideal for venting many of today's harsh chemicals
- Available with a polyurethane (PU-75 shore material) clip cover to protect the helix & the equipment that is attached to the hose



