




M

r Fume Dust Material

FSP-5










- Single-ply PVC vinyl coated polyester fabric hose reinforced with a spring steel wire helix & external PVC wearstrip
- · Lightweight duct for blower applications
- Great compressibility with an 11:1 compressibility ratio
- Retractability allows for convenient storage & easy transport in a fraction of its fully extended length
- Wearstrip offers additional external abrasion & drag resistance
- · Listed as UL 94V-0 flame retardant
- Manufactured with materials that meet NFPA 701 standards
- · Shown with optional cuff



SD-W









- Single-ply neoprene coated polyester fabric hose reinforced with a spring steel wire helix & external PVC wearstrip
- Ideal for moving large volumes of air in portable or permanent ventilation/exhaust systems
- Wearstrip offers additional external abrasion & drag resistance
- Great compressibility
- Retractability allows for convenient storage & easy transport in a fraction of its fully extended length
- · Listed as UL 94V-0 flame retardant
- Available in a self-retracting version (STO), 4" to 8" only
- · Shown with optional cuff



SD

Size Range (In) stock 4" to 24' custom to 60'
Standard Length (Ft) 25
Standard Colors
Temperature Range (°F)65° to 250°



®JU

- Single-ply neoprene coated polyester fabric hose reinforced with a spring steel wire helix
- Ideal for moving large volumes of air in portable or permanent ventilation/exhaust systems
- · Great compressibility
- Retractability allows for convenient storage & easy transport in a fraction of its fully extended length
- · Listed as UL 94V-0 flame retardant
- Shown with optional cuff



Springflex® End Finishes

Flexaust offers a variety of end finishes including several types of fabric cuffs for the Springflex[®] product line. Assembling hoses with various types of required end finishes is another way in which Flexaust services its customers and reduces costs.



Sewn Cuff



Standard/Enclosed Belted Cuff