

NS



Size Range (In) stock 1" to 8"
Standard Length (Ft) 12'
Standard Colors iron oxide red inner layer
black outer layer
Temperature Range (°F) -65° to 550°



- Double-ply fabric hose with a silicone coated fiberglass inner layer & a silicone coated Nomex® outer layer reinforced with a spring steel wire helix & external filament fiberglass cord
- Nomex® material increases flex life & abrasion resistance
- Suited for high temperature air handling applications
- The narrow pitch allows for tight bending radius while maintaining a smooth air flow
- Ideal for applications where constant flexing is involved
- Non-kinking
- Resistant to many oils & solvents, ozone, water, fungus & alkalis



GN




Size Range (In) stock 1" to 8"
Standard Length (Ft) 12'
Standard Colors black
Temperature Range (°F) -40° to 300°



- Double-ply neoprene coated fiberglass fabric hose reinforced with a spring steel wire helix & external filament fiberglass cord
- Offers higher temperature characteristics than traditional neoprene hoses
- The narrow pitch allows for tight bending radius while maintaining a smooth air flow
- Non-kinking
- Not recommended for continuous flexing



Flex-Vest®



Size Range (In) stock 1" to 6"
custom to 8"
Standard Length (Ft) 12'
custom to 25"
Standard Colors iron oxide red inner layer
black outer layer
Temperature Range (°F) . . -65° to 550° inner layer
intermittent to 600°
-40° to 250° outer layer



- Inner Layer; Double-ply silicone coated fiberglass fabric hose reinforced with a spring steel wire helix
- Outer layer; Single-ply neoprene coated polyester fabric hose reinforced with a spring steel wire helix
- Insulation; 1-inch fiberglass insulation (R Value=4)
- Insulated dryer hose
- Combines flexibility with minimal heat loss
- Suited for air handling applications at low positive & low negative pressures
- Good flexibility
- Excellent chemical resistance



Raceflex®



Inside Diameter (In) stock 1½" to 3"
custom to 8"
Standard Length (Ft) 12'
Standard Colors silver
Temperature Range (°F) -65° to 625°



- Light weight laminate of fiberglass & vacuum metallized polyester film
- Heat reflective to 625°F
- Light weight & flexible
- Smooth bend radius
- 2.64-inch compression per foot of hose
- Designed for brake ducting & ventilation of drive compartments in racecars

