


DFD-T




Size Range (In)stock 1", 1¼", 1½",
1¾", 2", 2½", 3", 4"
Standard Length (Ft) 25', 50'
Standard Colors black
Temperature Range (°F) -40° to 225°



- Light weight plastic thermoplastic rubber hose reinforced with an internal polypropylene helix
- Pliable helix can be formed to fit various applications
- Flexible, crush resistant & compressible
- Meets FMVSS 302 flame standards
- Great choice for heater/defroster & ventilation applications
- Can also be manufactured with PVC materials



FTE-T



Size Range (In)stock 1", 1¼", 1½",
1¾", 2", 2½", 3", 4"
Standard Length (Ft) 25', 50'
Standard Colors black with gray helix
Temperature Range (°F) -60° to 275°
intermittent to 300°



- Light weight thermoplastic rubber hose reinforced with an external polypropylene wearstrip
- Very smooth interior assures minimal friction loss & efficient air flow
- Very flexible & crush resistant
- Can also be manufactured in FDA, polyurethane & PVC elastomer materials
- Ideal for dust collection, fume exhaust & conduit applications



Dayflex® Accessories

Genesis® Screw Cuffs available on MG-V and MG-U. See page 15 for more information.



Additional Products

Flexaust is excited to offer a variety of Hose & Ducting products for a wide range of applications. While we feature our most popular products in this catalog, we also offer multiple manufacturing constructions and processes to service many industries. Please ask the Flexaust Sales Team about our:

- Self-retracting hose
- Stretch hose
- Static hose
- Special design duct cleaning hoses
- Floor care vacuum hoses
- Special metric diameters
- Blow molded hose
- Injection molding
- Square and rectangular hose ends
- Insulation hose
- Flat belts (for the vacuum industry)