

DC Series

Large capacity reels for general and industrial use. Ideal for production lines, material handling equipment, service areas, maintenance applications and service vehicles. Suitable for mounting up to 20' above floor level.

- Steel construction for long life in industrial applications
- Containerized main spring for safe, easy maintenance
- Adjustable guide arm
- Four roller guide to protect hose
- Brass, nickel and zinc fluid path
- Durable epoxy powder-coat finish
- Ratchet lock and easy tension adjustment
- Hose stop included with all models
- Nitrile seals

For dimensions, see page 20



DC

Notes: Spool hose connection fittings must be Female NPSM. Reels are primarily for manual pullout applications with lift height no more than 20ft. Otherwise, please call factory for application assistance.

Standard Model	Hose inlet fitting (NPT)	Hose Inner Diameter	Length		Pressure
			ft.	m	PSI
DC475	1/2"	1/2"	75	22.9	300
DC410	1/2"	1/2"	100	30.5	300
DC400	1/2"	Without Hose			300
DC660	3/4"	3/4"	60	18.3	300
DC600	3/4"	Without Hose			300
DC850	1"	1"	50	15.2	300
DC800	1"	Without Hose			300

Hose Specs

Type: EPDM/SBR tube
 Black SBR cover
 Max Temp: 176° F (80°C)