





- Sales Tip: The amount of slip resistance required, and exposure to chemicals, oils, and greases are the key determining factors when choosing between GSII™ or Niru® Cushion-Ease® products
- Where to Specify: (650) Intended for harsh wet environments where industrial chemicals, oils, greases, and animal fats are often found. (656) should be recommended for industrial applications where exposure to chemicals, oils, greases, and animal fats can create slip hazards.
- 100% Nitrile rubber compound provides the highest degree of resistance to chemicals, oils, and greases
- Available in perforated (650), or solid top (656) versions
- 650 has a large hole drainage system that facilitates the removal of liquid and debris from the work area
- 656 offers solid-top construction for additional anti-fatigue relief, and is easy to clean
- Overall thickness is 3/4"
- Modular design is compatible with NoTrax® 551 M.D. Ramp System and can accommodate a variety of custom configurations (see page 22 for more information)



RESULTS from INDEPENDENT TEST LABS & PRESENTED as COMPARISONS to OTHER NoTRAX® INDUSTRIAL MATS #650

#656



#650/656 Niru [®] Cushion-Ease [®] Solid			
Stock Size	3' x 3'	3' x 5'	
List Price #650	\$111.20	\$185.34	
Weight (lbs.)	24	39	
List Price #656	\$111.20	N/A	
Weight (lbs.)	24	N/A	

Shipping Location: Superior Manufacturing Group - Chicago, IL 60638

GOODYEAR Call Toll Free: 1-866-711-4673

