

# Superkrimp



Hose  
**A**

Fittings  
**B**

Parkrimp Equipment  
**C**

Accessories  
**D**

Technical  
**E**

## Features

- Easy to use table top design
- Engineered for optimal durability
- Crimps both steel and stainless steel fittings
- For use with 25, 26, 43, 70, 71, 73, 76, 78, 79, 81, and HY Series fittings

## Specifications

- Dimensions: 20" wide, 31" deep, 41" high
- Weight: 600 lbs
- Rating: 70 ton force @ 5,000 psi maximum
- Full Cycle Time: 20 seconds without adapter bowl  
15 seconds with adapter bowl
- Hydraulic oil: Enerpac oil

## Standard Equipment

Part Number		Description	Individual Part Number
88C-081	88C-082		
●		Superkrimp crimper with 230/460 volt, 3 phase, 50/60 Hz power unit wired for 230 volts	
	●	Superkrimp crimper with 230/460 volt, 1 phase, 50/60 Hz power unit wired for 230 volts	
●	●	Adapter bowl	83C-OCB
●	●	Spacer ring	83C-R02
●	●	Spacer Plate	83C-R02H

## Optional Tooling

- Die Kit (88C-KDA)
- Includes 43 Series dies in sizes 1/4", 3/8", 1/2", 3/4", 1" and 1-1/4" and 70/71 Series dies in sizes 3/8", 1/2", 3/4", 1", 1-1/4" and 1-1/2" **ONLY**.

**Note:**

- For crimp instructions, see pages C-16 and C-17.
- Hose assemblies must be inspected for cleanliness and free of all foreign particles.
- Parker Hannifin will not accept responsibility for the operation of, or provide warranty coverage for, a crimper that is operated by a power unit other than equipment supplied by Parker Hannifin for the express purpose of operating the crimper.