


## Accessory Selection Guide – Firesleeve (FS-F)

Parker Firesleeve is a flame resistant sheath that protects the hose from extreme temperature conditions. Firesleeve easily slides over hoses and readily expands over fitting. It can be assembled with Parker FSC or properly sized wormgear clamp.

**Construction:** Braided fiberglass sleeve and an orange, bonded and seamless silicone rubber cover.

**Specifications:** Conforms to SAE Aerospace Standard 1072A Type 2A.

**Temperature Range:** -54°C to +260°C (-65°F to +500°F).



**Note:** The Firesleeve inside dimension (I.D.) must exceed the outside diameter (O.D.) of the hose and offer an allowance for easy hose insertion. For example, 201-16 has a 1.23 in. O.D. FS-S-24, with an I.D. of 1.46 in., is the suggested Firesleeve.

**Note:** Parker FSC Clamp fits all hoses up to 2 in. O.D.

**Note:** Parker HC Clamps (wormgear) are listed on page D-24.



Firesleeve (FS-F)



FSC Clamp

Part Number: FSC  
(One size fits all hoses up to 2 inch O.D.)

Part Number	Inside Dia. inch	201, 221FR		302		422, 424, 426 431, 436, AX		701		801	
		206, 225 244 266	213 285 293	301LT 304, 341 BXX	351TC/ST 451TC/ST 471TC/ST 482TC/ST	421WC	601	721 721TC 772TC/ST 774	731 P35, 781 782TC/ST 791TC 792TC/ST	804 821 821FR 831 836	811 881 811HT
FS-F-10	0.58	-4	-4	-3	-3/-4	-3	-3				-4
FS-F-11	0.65	-5	-5	-4	-5	-4	-4				
FS-F-12	0.71		-6	-5							-6
FS-F-14	0.84	-6/-8	-8	-6	-6	-6	-5/-6				-8
FS-F-16	0.96		-10		-8	-8		-6			
FS-F-18	1.08	-10	-12	-8/-10	-10	-8		-8			-10
FS-F-20	1.21	-12		-12	-12	-10		-10	-8		-12
FS-F-24	1.46				-16						
FS-F-30	1.84	-24	-24								
FS-F-38	2.34	-32	-32	-20/-24	-24			-20/-24	-20		-24
FS-F-40	2.46								-24		

**Note:** See Page D-22 for Firesleeve assembly instructions.

Hose  
**A**

Fittings  
**B**

Equipment  
**C**

Accessories  
**D**

Technical  
**E**