

A Application

Standard Fitting Configurations by Connection and End Code

	Description	End Code	
Pipe	Male NPTF Pipe - Rigid - Straight	01	
	Male NPTF Pipe - Swivel - Straight	13	
	Male NPTF Pipe - Swivel - 90° Elbow	1L	
	Male API Pipe - Rigid - Straight	AP	
	Female NPTF Pipe - Rigid - Straight	02	
	Female NPSM Pipe - Swivel - Straight (60° Cone)	07	
	Female NPTF Pipe - Swivel - Straight	S2	
	Female NPSM Pipe - Gasket Joint - Swivel - Straight	7G	
	Female Grease Connection - SPL-PTF Taper Thread - Rigid Straight - 1/2 x 27	GJ	
	Male NPTF Pipe - Rigid - 45° Elbow	31	
Male NPTF Pipe - Rigid - 90° Elbow or Side Outlet	21		
SAE Str. Thr.	Male SAE Straight Thread with O-Ring - Rigid - Straight	05	
	Male SAE Straight Thread with O-Ring - Swivel - Straight	0G	
	Male SAE Straight Thread with O-Ring - Adjustable - 45° Elbow	25	
	Male SAE Straight Thread with O-Ring - Swivel - 90° Elbow	0L	
	Male SAE Straight Thread with O-Ring - Adjustable - 90° Elbow	35	
Flare	Male JIC 37° - Rigid - Straight	03	
	Male JIC 37° - Bulkhead without Locknut - Straight	LB	
	Female JIC 37° - Swivel - Straight	06	
	Female JIC 37° - Swivel - 45° Elbow - Short Drop	37	
	Female JIC 37° - Swivel - 45° Elbow - Medium Drop	L7	
	Female JIC 37° - Swivel - 90° Elbow - Short Drop	39	
	Female JIC 37° - Swivel - 90° Elbow - Medium Drop	L9	
	Female JIC 37° - Swivel - 90° Elbow - Long Drop	41	
	Female JIC 37° - Swivel - Straight	48	
	Female JIC 37° - Swivel - 150° Elbow	4V	
	Male SAE 45° - Rigid - Straight	04	
	Female SAE 45° - Swivel - Straight	08	
	Female SAE 45 / Swivel - 45° Elbow	77	
	Female SAE 45 / Swivel - 90° Elbow	79	
	Female SAE 45 / Swivel - 90° Elbow - Long Drop	81	
	Female JIC 37°/SAE 45° Dual Flare - Swivel - Straight	68	
	Inverted Flare	Male Inverted SAE 45° - Swivel - Straight	28
		Male Inverted SAE 45° - Swivel - 45° Elbow	67
Male Inverted SAE 45° - Swivel - 90° Elbow		69	
Male Inverted SAE 45° - Swivel - 90° Elbow - Long (In-Line)		71	
Tube-O	Female Inverted SAE 45° - Rigid - Straight	29	
	Male Tube-O - Swivel - Straight - Short Pilot	S5	
Tube-O	Male Tube-O - Swivel - Straight - Short Pilot with Charge Port for R12	S5-PR	
	Male Tube-O - Swivel - Straight - Long Pilot	45	
	Male Tube-O - Swivel - Straight - Long Pilot with Charge Port for R12	45-PR	

	Description	End Code
Tube-O	Male Tube-O - Swivel - Straight - Long Pilot with Charge Port for R134a	45-PT
	Female Tube-O - Swivel - 90° Elbow - Long Pilot	5L
	Female Tube-O - Swivel - 90° Elbow - Long Pilot with Charge Port for R12	5L-PB
	Female Tube-O - Swivel - 90° Elbow - Long Pilot with Charge Port for R12	5L-PR
	Female Tube-O - Swivel - 90° Elbow - Long Pilot with Charge Port for R134a	5L-PT
	Male Tube-O - Swivel - 90° Elbow - Long Pilot	5M
	Male Tube-O - Swivel - 90° Elbow - Long Pilot with Charge Port for R12	5M-PR
	Male Tube-O - Swivel - 90° Elbow - Long Pilot with Charge Port for R134a	5M-PT
	Male Tube-O - Swivel - 90° Elbow - Long Pilot with Charge Port for R134a	5M-PV
	Male Tube-O - Rigid - Straight - Internal Long Pilot (3-Step)	5G
	Male Tube-O - Rigid - Straight - Internal Long Pilot (3-Step) with Charge Port for R12	5G-PR
	Male Tube-O - Swivel - 45° Elbow - Short Pilot	5R
	Male Tube-O - Swivel - 45° Elbow - Long Pilot	5P
	Male Tube-O - Swivel - 45° Elbow - Long Pilot with Charge Port for R134a	5P-PT
	Male Tube-O - Swivel - 90° Elbow - Short Pilot	5K
	Male Tube-O - Swivel - 90° Elbow - Short Pilot with Charge Port for R134a	5K-PB
	Male Tube-O - Swivel - 90° Elbow - Short Pilot with Charge Port for R12	5K-PR
	Compressor	Female Tube-O - Swivel - Straight - Short Pilot
Female Tube-O - Swivel - Straight - Long Pilot		59
Female Tube-O - Swivel - Straight - Long Pilot with Charge Port for 134a		59-PB
Female Tube-O - Swivel - Straight - Long Pilot with Charge Port		59-PT
Female Tube-O - Swivel - 45° Elbow - Short Pilot		5H
Female Tube-O - Swivel - 45° Elbow - Long Pilot		5N
Female Tube-O - Swivel - 45° Elbow - Long Pilot with Charge Port		5N-PB
Female Tube-O - Swivel - 45° Elbow - Long Pilot with Charge Port		5N-PT
Female Tube-O - Swivel - 90° Elbow - Short Pilot		5T
Female Compressor - Swivel - 45° Elbow		5V
Female Compressor - Swivel - 90° Elbow		5W
Female Compressor - Swivel - 90° Elbow - Block Type		5Z
Female Compressor - Swivel - 135° Elbow	RV	
Female Compressor - Swivel - 180° Elbow - Block Type	RZ	
Male SAE Compression Seat (without Nut or Sleeve)	61	
Two Hole (2.25" X 0.44") Flange - Rigid - 90° Elbow	2H	
Flange	SAE Code 61 Flange Head - Straight	15
	SAE Code 61 Flange Head - Straight (5,000 psi)	4A
	SAE Code 61 Flange Head - 22½° Elbow -	16

Continued on next page

Hose

A

Fittings

B

Equipment

C

Accessories

D

Technical

E