

# A pplication

| METRIC to ENGLISH EQUIVALENTS  | ENGLISH to METRIC EQUIVALENTS |
|--|-------------------------------|
| inches x 25.4 = millimeters (mm)   |                               |
| inches x 2.54 = centimeters (cm)   |                               |
| feet x .3048 = meters (m)  |                               |
| yard x .9144 = meters (m)  |                               |
| psi x .0689 = bar  |                               |
| psi x .0069 = Megapascals (MPa)  |                               |
| psi x .0703 = Kilogram force per square centimeter<br>(Kgf/cm <sup>2</sup> ) |                               |
| pound force x 4.448 = Newtons  |                               |
| pound · inch x .113 = Newton · meters (N · m)                                |                               |
| pound · foot x 1.356 = Newton · meters (N · m)                               |                               |
| millimeter x .0394 = inch (in)   |                               |
| centimeter x .3937 = inch (in)   |                               |
| meters x 3.281 = feet (ft)   |                               |
| meters x 1.0936 = yards (yd)   |                               |
| bar x 14.5 = psi   |                               |
| Megapascals x 145.0 = psi  |                               |
| Kilogram force per square centimeter x 14.22 = psi                           |                               |
| Newton · meter x .2248 = pounds force (lbf)                                  |                               |
| Newton · meter x 8.850 = pound · inches (lb · in)                            |                               |
| Newton · meter x .737 = pound feet (lb · ft)                                 |                               |

## Metric Conversion

| METRIC I.D. KIT   |
|---|
| INTERNATIONAL HOSE FITTING IDENTIFICATION KIT   |
| The booklet, gauges and caliper contained in this fitting I.D. Kit, can be used to identify most types of hydraulic hose fittings and adapters including:<br><br>U.S. Standards<br>British Standard Pipe<br>German (DIN) Metric<br>French Metric and GAZ<br>Japanese Standards (JIS)<br><br>Contents of Kit:<br><br>Instruction Book with Tables<br>Screw Pitch Gauge for U.S. Threads<br>International Gauge for Metric and British Threads<br>Inch and Millimeter Caliper<br>Carry Case |

| MILLIMETERS to FRACTIONS to DECIMALS |          |         |         |          |         |         |          |         |         |          |         |
|--------------------------------------|----------|---------|---------|----------|---------|---------|----------|---------|---------|----------|---------|
| MM                                   | INCHES   |         | MM      | INCHES   |         | MM      | INCHES   |         | MM      | INCHES   |         |
|                                      | FRACTION | DECIMAL |         | FRACTION | DECIMAL |         | FRACTION | DECIMAL |         | FRACTION | DECIMAL |
| 0.3969                               | 1/64     | 0.0156  | 6.7469  | 17/64    | 0.2656  | 13.0969 | 33/64    | 0.5156  | 19.4469 | 49/64    | 0.7656  |
| 0.7938                               | 1/32     | 0.0312  | 7.1438  | 9/32     | 0.2812  | 13.4938 | 17/32    | 0.5312  | 19.8438 | 25/32    | 0.7812  |
| 1.1906                               | 3/64     | 0.0468  | 7.5406  | 19/64    | 0.2968  | 13.8906 | 35/64    | 0.5468  | 20.2406 | 51/64    | 0.7968  |
| 1.5875                               | 1/16     | 0.0625  | 7.9375  | 5/16     | 0.3125  | 14.2875 | 9/16     | 0.5625  | 20.2375 | 13/16    | 0.8125  |
| 1.9844                               | 5/64     | 0.0781  | 8.3344  | 21/64    | 0.3281  | 14.6844 | 37/64    | 0.5781  | 21.0344 | 53/64    | 0.8281  |
| 2.3812                               | 3/32     | 0.0937  | 8.7312  | 11/32    | 0.3437  | 15.0812 | 19/32    | 0.5937  | 21.4312 | 27/32    | 0.8437  |
| 2.7781                               | 7/64     | 0.1093  | 9.1281  | 23/64    | 0.3593  | 15.4781 | 39/64    | 0.6093  | 21.8281 | 55/64    | 0.8593  |
| 3.1750                               | 1/8      | 0.1250  | 9.5250  | 3/8      | 0.3750  | 15.8750 | 5/8      | 0.6250  | 22.2250 | 7/8      | 0.8750  |
| 3.5719                               | 9/64     | 0.1406  | 9.9219  | 25/64    | 0.3906  | 16.2719 | 41/64    | 0.6406  | 22.6219 | 57/64    | 0.8906  |
| 3.9688                               | 5/32     | 0.1562  | 10.3188 | 13/32    | 0.4062  | 16.6688 | 21/32    | 0.6562  | 23.0188 | 29/32    | 0.9062  |
| 4.3656                               | 11/64    | 0.1718  | 10.7156 | 27/64    | 0.4218  | 17.0656 | 43/64    | 0.6718  | 23.4156 | 59/64    | 0.9218  |
| 4.7625                               | 3/16     | 0.1875  | 11.1125 | 7/16     | 0.4375  | 17.4625 | 11/16    | 0.6875  | 23.8125 | 15/16    | 0.9375  |
| 5.1594                               | 13/64    | 0.2031  | 11.5094 | 29/64    | 0.4531  | 17.8594 | 45/64    | 0.7031  | 24.2094 | 61/64    | 0.9531  |
| 5.5562                               | 7/32     | 0.2187  | 11.9062 | 15/32    | 0.4687  | 18.2562 | 23/32    | 0.7187  | 24.6062 | 31/32    | 0.9687  |
| 5.9531                               | 15/64    | 0.2343  | 12.3031 | 31/64    | 0.4843  | 18.6531 | 47/64    | 0.7343  | 25.0031 | 63/64    | 0.9843  |
| 6.3500                               | 1/4      | 0.2500  | 12.7000 | 1/2      | 0.5000  | 19.0500 | 3/4      | 0.7500  | 25.4000 | 1        | 1.0000  |