



Applications

 Oil Mist Lubricating Air Lines

GST® II General Service Air & Water Hose

7031 (Green) / 7057 (Blue) / 7092 (Red) 7093 (Black) / 7096 (Yellow)

An economical and versatile general purpose hose, which is excellent for air and water service as well as many agricultural chemicals including LASSO® herbicide. The EPDM tube and cover resists heat, sunlight, ozone and weathering. The GST II hose exceeds RMA class C medium oil resistance requirements. Suitable for applications such as oil mist lubricating air lines, but NOT suitable for the transfer of petroleum products. Closely plied reinforcement of high tensile textile cord provides excellent coupling retention and kink resistance. 4:1 Design factor

>> Available in several colors for application coding. **Excellent weathering resistance withstands** exposure to the elements.

Tube	Black EPDM
Cover	EPDM - colors referenced above
Reinforcement	Multiple textile spirals
Temperature Range	-40°F to +212°F (-40°C to +100°C)
Branding Example	PARKER SERIES 7031 GST® II I.D. (IN & MM) XXX PSI MAX WP MADE IN USA
Brand Description	Ink Brand - White letter color
Compare to	Goodyear Horizon General Purpose; Gates Adapta Flex; Boston Bosflex A/W; Thermoid Valuflex GS

LENGTHS: Reels are 90% 1 piece, 10% 2 pieces, 50 ft. min. length (total footage on reel is +50 ft./-0 ft. of length indicated). All 50 ft. lengths are coiled, tied and secured in cartons per order.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7611, 7615, 7692, 7628, 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.