



Applications

- Electric **Furnaces**
- Pot Lines

MPT® II Multi-Purpose-Oil Resistant Air & Water Hose - Non-Conductive

Series 7094 (Red) / 7095 (Black)

MPT® II is a premium high quality, economical, multi-purpose hose that is oil resistant, excellent for air and water service and many chemicals. Closely plied reinforcement of high tensile textile cord provides excellent coupling retention and kink resistance. The hose is electrically non-conductive with a minimum resistance of one megohm per inch at 1000 volts DC. MPT II hose exceeds RMA Class A-High Oil Resistance requirements. **NOTE: Do not use for hot, dry air applications.** 4:1 Design factor

>> Highly oil resistant and non-conductive

Tube	Black Nitrile
Cover	Red or Black Neoprene
Reinforcement	Multiple textile spirals
Temperature Range	-20°F to +212°F (-29°C to +100°C)
Branding	PARKER SERIES 7094 MPT® II 3/16 ID (4.8 MM) XXX PSI MAX WP MADE IN USA - ELECTRICALLY NON-CONDUCTIVE
Brand Description	Ink Brand - White letter color
Compare to	Boston Shock Safe; Goodyear Ortac/Wingfoot; Gates PremoFlex/19B

LENGTHS: All reels are 90% 1 piece, 10% 2 pieces, 50 ft. min. length (total footage on reel is +50 ft./-0 ft. of length indicated). All 50 ft. lengths are coiled, tied and secured in cartons per order.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7611, 7615, 7692, 7628, 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.