

MPT® II
Multi-Purpose—Oil Resistant
Air & Water Hose - Non-Conductive
Series 7094 (Red) / 7095 (Black)



7094



7095

Part No.	ID (in.)	ID (mm)	Reinf. Spirals	OD (in.)	OD (mm)	Approx Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
-19200	3/16	4.8	2	0.437	11.1	5	1.8	200
-19300	3/16	4.8	2	0.437	11.1	5	1.8	300
-25200	1/4	6.4	2	0.500	12.7	9	2.0	200
-2520050	1/4	6.4	2	0.500	12.7	9	2.0	200
-25300	1/4	6.4	2	0.550	14.0	12	2.5	300
-2530050	1/4	6.4	2	0.550	14.0	12	2.5	300
-31200	5/16	7.9	2	0.594	15.1	13	3.0	200
-3120050	5/16	7.9	2	0.594	15.1	13	3.0	200
-31300	5/16	7.9	2	0.594	15.1	13	3.3	300
-3130050	5/16	7.9	2	0.594	15.1	13	3.3	300
-38200	3/8	9.5	2	0.656	16.7	15	3.8	200
-3820050	3/8	9.5	2	0.656	16.7	15	3.8	200
-38300	3/8	9.5	2	0.688	17.5	17	3.8	300
-3830050	3/8	9.5	2	0.688	17.5	17	3.8	300
-50200	1/2	12.7	2	0.813	20.7	21	5.0	200
-5020050	1/2	12.7	2	0.813	20.7	21	5.0	200
-50250	1/2	12.7	2	0.844	21.4	22	5.0	250
-5025050	1/2	12.7	2	0.844	21.4	22	5.0	250
-50304	1/2	12.7	4	0.875	22.2	26	5.0	300
-5030450	1/2	12.7	4	0.875	22.2	26	5.0	300
-63200	5/8	15.9	2	0.969	24.6	36	5.5	200
-6320050	5/8	15.9	2	0.969	24.6	36	5.5	200
-63304	5/8	15.9	4	1.062	27.0	37	6.1	300
-6330450	5/8	15.9	4	1.062	27.0	37	6.1	300
-75200	3/4	19.1	2	1.109	28.2	34	7.5	200
-7520050	3/4	19.1	2	1.109	28.2	34	7.5	200
-75304	3/4	19.1	4	1.156	29.4	39	6.0	300
-7530450	3/4	19.1	4	1.156	29.4	39	6.0	300
-100200	1	25.4	4	1.406	35.7	50	10.0	200
-10020050	1	25.4	4	1.406	35.7	50	10.0	200
-100304	1	25.4	4	1.438	36.5	54	8.0	300
-10030450	1	25.4	4	1.438	36.5	54	8.0	300
-125204	1 1/4	31.75	4	1.781	45.2	77	9.0	200
-125304	1 1/4	31.75	4	1.781	45.2	90	9.0	300
-150204	1 1/2	38.1	4	2.031	51.6	86	10.0	200
-150304	1 1/2	38.1	4	2.031	51.6	91	10.0	300