



# SUPER MPT Hose

## Series 7396 (Red) / 7397 (Black)

A premium oil resistant multi-purpose hose that is a rigid mandrel construction, which produces a TRUE round, concentric hose. Superior adhesion of the hose layers provides endurance in tough applications. All of this added with SUPER flexibility for easier handling. The tube is rated for RMA Class A-High Oil Resistance. The hose is electrically non-conductive with a minimum resistance of one megohm per inch at 1000 volts DC. **NOTE: Do not use for hot, dry air applications.**


4:1 Design factor

### >> Class A oil resistance, extremely flexible

<b>Tube</b>	Black Nitrile Rubber
<b>Cover</b>	Black or Red Neoprene
<b>Reinforcement</b>	Multiple textile plies
<b>Temperature Range</b>	-20°F to +212°F (-29°C to +100°C)
<b>Branding</b>	PARKER SERIES 7396 SUPER MPT MULTI-PURPOSE HOSE XXX PSI MAX WP ELECTRICALLY NON-CONDUCTIVE MADE IN USA
<b>Brand Description</b>	Tape Brand - White letters
<b>Compare to</b>	Gates Duroflex; Goodyear Ortac 250

**LENGTHS:** 50 ft. and 200 ft. coils. Reels are 2 pieces, 200 ft. per length/400 ft. per reel. Tied and plastic tire wrapped.

**COUPLINGS:** For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692, 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.



7396

7397

### Applications

- Transfer of Air, Oil and Water

Part No.	Pkg.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
-125200200	200'	1¼	31.8	2	1.741	44.2	70	7.5	200
-12520050	50'	1¼	31.8	2	1.741	44.2	70	7.5	200
-125200100	100'	1¼	31.8	2	1.741	44.2	70	7.5	200
-125200A	reel	1¼	31.8	2	1.741	44.2	70	7.5	200
-150200200	200'	1½	38.1	2	1.985	50.4	80	8.5	200
-15020050	50'	1½	38.1	2	1.985	50.4	80	8.5	200
-150200100	100'	1½	38.1	2	1.985	50.4	80	8.5	200
-150200A	reel	1½	38.1	2	1.985	50.4	80	8.5	200
-200200200	200'	2	50.8	4	2.568	65.2	122	12.0	200
-20020050	50'	2	50.8	4	2.568	65.2	122	12.0	200
-200200100	100'	2	50.8	4	2.568	65.2	122	12.0	200
-125300200	200'	1¼	31.8	4	1.798	45.7	79	7.5	300
-12530050	50'	1¼	31.8	4	1.798	45.7	79	7.5	300
-125300100	100'	1¼	31.8	4	1.798	45.7	79	7.5	300
-125300A	reel	1¼	31.8	4	1.798	45.7	79	7.5	300
-150300200	200'	1½	38.1	4	2.025	51.4	87	8.5	300
-15030050	50'	1½	38.1	4	2.025	51.4	87	8.5	300
-150300100	100'	1½	38.1	4	2.025	51.4	87	8.5	300
-150300A	reel	1½	38.1	4	2.025	51.4	87	8.5	300
-200300200	200'	2	50.8	4	2.600	66.0	129	12.0	300
-20030050	50'	2	50.8	4	2.600	66.0	129	12.0	300
-200300100	100'	2	50.8	4	2.600	66.0	129	12.0	300



**WARNING!** Combination nipple and bands reduce the working pressure of the assembly to less than the hose's maximum working pressure. Refer to NAHAD Assembly Guidelines for working pressure.