



THORO-FLO® Multi-Purpose Hose

Series 7101 (Red) / 7119 (Black)

A tough, versatile, multi-purpose hose designed to handle many jobs. The tube is compounded to provide maximum oil resistance. THORO-FLO® hose may be used to transmit air, water, oil and many chemicals in service up to 300 PSI. Exceeds RMA - Class A Oil resistance. **NOTE: Do not use for hot, dry air applications.**
4:1 Design factor

>> Superior kink and stretch resistance

| | |
|-------------------|--|
| Tube | Black Nitrile |
| Cover | Black or Red Neoprene |
| Reinforcement | One or multiple textile braids |
| Temperature Range | -20°F to +212°F (-29°C to +100°C) |
| Branding | PARKER SERIES 7101 THORO-FLO® 1/4 ID (6.4 MM) XXX PSI MADE IN USA |
| Brand Description | Ink Brand - White letter color |
| Compare to | Thermold Maxecon/GP |

LENGTHS: Random lengths on 650 ft. reels, 725 ft. max., 400 ft. min., with 50 ft. min. length, max 3 pieces.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7611, 7615, 7692, 7628. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.



7101



7119

Applications

- Transfer of Air, Oil and Water
- Hose Reels

| Part No. | ID (in.) | ID (mm) | Reinf. Layers | ID (in.) | ID (mm) | Approx. Wt. per 100 Ft. | Min. Bend Radius | Max. Rec. WP |
|----------|----------|---------|---------------|----------|---------|-------------------------|------------------|--------------|
| -251 | 1/4 | 6.4 | 1 | 0.500 | 12.7 | 9 | 2.5 | 250 |
| -252 | 1/4 | 6.4 | 2 | 0.594 | 15.1 | 15 | 3.3 | 300 |
| -311 | 5/16 | 7.9 | 1 | 0.625 | 15.9 | 14 | 3.3 | 250 |
| -312 | 5/16 | 7.9 | 2 | 0.656 | 16.7 | 17 | 3.5 | 300 |
| -381 | 3/8 | 9.5 | 1 | 0.687 | 17.4 | 17 | 3.5 | 250 |
| -382 | 3/8 | 9.5 | 2 | 0.719 | 18.3 | 19 | 4.0 | 300 |
| -501 | 1/2 | 12.7 | 1 | 0.812 | 20.6 | 21 | 4.5 | 250 |
| -502 | 1/2 | 12.7 | 2 | 0.875 | 22.2 | 26 | 4.8 | 300 |