



DAY-FLO® Special Purpose Hose Series 7134 (Red) / 7187 (Black)

A tough, versatile, multi-purpose hose designed to handle many jobs. The tube is compounded to provide maximum oil resistance. DAY-FLO® hose may be used to transfer air, water, oil and many chemicals in service up to 300 PSI. Tube exceeds RMA - Class A Oil resistance. Braided reinforcement for maximum kink resistance. **NOTE: Do not use for hot, dry air applications.**

4:1 Design factor

>> Superior kink and stretch resistance

Tube	Black Nitrile
Cover	Black or Red Neoprene
Reinforcement	One or multiple textile braids
Temperature Range	-20°F to +212°F (-29°C to +100°C)
Branding	PARKER SERIES 7134 DAY-FLO® 3/16 ID (4.8 MM) XXX PSI MAX WP MADE IN USA
Brand Description	Ink Brand - White letter color
Compare to	Gates 19B Plantmaster; Boston Perfection 300

LENGTHS: Random lengths on 500 ft. nominal reels, 725 ft. max, 400 ft. min. 3 pieces max., with 50 ft. min. length.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7611, 7615, 7692, 7628. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.



7134



7187

Applications

- Transfer of Air, Oil and Water
- Hose Reels

Part No.	ID (in.)	ID (mm)	Reinf. Braids	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
-191	3/16	4.8	1	0.437	11.1	8	2.0	250
-251	1/4	6.4	1	0.500	12.7	9	2.5	250
-252	1/4	6.4	2	0.594	15.1	15	3.3	300
-311	5/16	7.9	1	0.625	15.9	14	3.0	250
-312	5/16	7.9	2	0.656	16.7	17	3.5	300
-381	3/8	9.5	1	0.687	17.4	17	3.5	250
-382	3/8	9.5	2	0.719	18.3	19	4.0	300
-501	1/2	12.7	1	0.812	20.6	21	4.5	250
-502	1/2	12.7	2	0.875	22.2	26	4.8	300