



WHIPPET® 200 Air Hose

Series 7137

Designed for light duty air lines and air hose whip ends. It is lightweight, flexible and oil resistant - ideal for industrial bench work.

4:1 Design factor

>> Lightweight and kink resistant

Tube	Black Nitrile
Cover	Black Neoprene
Reinforcement:	One textile braid
Temperature Range	-40°F to +180°F (-40°C to +82°C)
Branding	AIR SERVICE 200 PSI WP (DATE CODE)
Brand Description	Ink Brand - White letter color
Compare to	Goodyear Horizon 200; Boston Easy Couple

LENGTHS: ¼ in. = 400 ft. - 725 ft. 5 pieces max, with 50 ft. min. length; 5/16 in. & 3/8 in. = 400 ft. - 725 ft. 3 pieces max, with 50 ft. min. length.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7611, 7692, 7628. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Braids	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7137-251	¼	6.4	1	0.437	11.1	7	2.0	200
7137-311	5/16	7.9	1	0.531	13.5	9	2.5	200
7137-381	3/8	9.5	1	0.625	15.9	11	3.5	200

7137

Applications

- Hose Whips
- Air Tools
- Light-duty Air Service