



## MAXIFLEX® Air Hose

### Series 7308

MAXIFLEX® hose is light and flexible, yet sufficiently rugged to withstand the abuse and hard service found in mining and construction. It has excellent resistance to abrasion, gouging and weathering.

3:1 Design factor

### >> Abrasion resistant for tough environments

<b>Tube</b>	Black SBR
<b>Cover</b>	Yellow SBR
<b>Reinforcement</b>	Multiple textile plies
<b>Temperature Range</b>	-20°F to +200°F (-29°C to +93°C)
<b>Branding</b>	PARKER SERIES 7308 MAXIFLEX AIR HOSE 250 PSI WP MADE IN USA
<b>Brand Description</b>	Embossed Brand
<b>Compare to</b>	Goodyear Plicord Air 300

**LENGTHS:** 100 ft. lengths up to 200 ft. on quotation.

**COUPLINGS:** For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7308-1004	1	25.4	2	1.488	37.8	59	6.0	250
7308-1254	1¼	31.8	2	1.740	44.2	71	7.5	250
7308-1504	1½	38.1	2	2.031	51.6	95	8.5	250
7308-2004	2	50.8	4	2.598	66.0	134	14.0	250
7308-2504	2½	63.5	4	3.098	78.7	163	24.0	250
7308-3004	3	76.2	4	3.598	91.4	193	36.0	250

7308

### Applications

- Mining
- Construction
- Water and Air Transfer