



MAXIMAIRE® Heavy Duty Non-Conductive Air Hose Series 7201

This hose is designed for air drills and pneumatic service in mines, quarries, general construction and industrial jobs where a heavy duty braided hose is needed. Built with an oil resistant tube and an oil and abrasive resistant cover. Hose is electrically non-conductive with a minimum resistance of one megohm per inch at 1000 volts, DC. 4:1 Design factor

>> Non-conductive and rugged for industrial jobs

Tube	White Neoprene
Cover	Green Hypalon
Reinforcement	Multiple textile braids
Temperature Range	-20°F to +180°F (-29°C to +82°C)
Branding	PARKER USA 7201 MAXIMAIRE HEAVY DUTY AIR HOSE 2 1/2 ID XXX PSI MAX WP (DATE CODE)
Brand Description	Embossed Brand
Compare to	Goodyear Ortac 400; Boston Shock Safe, Mineforce

LENGTHS: Random lengths on reels. ½" and ¾" reels are 450 ft. – 550 ft. each and 1" reels are 400 ft. – 600 ft. All reels have a max. of 5 pieces, shortest piece 50 ft; 1¼" thru 2" 150 ft. in cartons max. of 3 pieces, 50 ft. min. length.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

7201

Applications

- Air Drills
- High Pressure Air Service
- Slurries

Part No.	ID (in.)	ID (mm)	Reinf. Braids	OD (in.)	OD (mm)	Approx. Wt. of 100 Ft.	Min. Bend Radius	Max. Rec. WP
7201-502A	½	12.7	2	0.938	23.8	31	5.0	500
7201-502050	½	12.7	2	0.938	23.8	31	5.0	500
7201-502100	½	12.7	2	0.938	23.8	31	5.0	500
7201-752A	¾	19.1	2	1.250	31.8	48	6.5	500
7201-752050	¾	19.1	2	1.250	31.8	48	6.5	500
7201-752100	¾	19.1	2	1.250	31.8	48	6.5	500
7201-1002A	1	25.4	2	1.562	39.7	70	8.0	500
7201-1002050	1	25.4	2	1.562	39.7	70	8.0	500
7201-1002100	1	25.4	2	1.562	39.7	70	8.0	500
7201-1252K	1¼	31.8	2	1.813	46.1	81	9.0	350
7201-1503K	1½	38.1	3	2.125	54.0	106	13.0	350
7201-2003K	2	50.8	3	2.656	67.5	153	15.0	350
7201-2503K	2½	63.5	3	3.250	82.6	210	22.0	300