



DRAGON BREATH® Hot Air Hose

Series 7281

This hose is specifically designed to convey hot air at +300° F continuous and +350° F intermittent from the compressor or blower on dry material unloading systems. The EPDM tube and cover offer excellent resistance to heat as well as to weather and ozone.

4:1 Design factor

>> Withstands high temperatures from compressors

Tube	Black EPDM
Cover	Black EPDM
Reinforcement	Multiple textile braids with helix wire
Temperature Range	-30°F to +300°/350°F (-34°C to +149°/177°C)
Branding	PARKER USA 7281 DRAGON BREATH® HOT AIR HOSE 1-1/2 ID 175 PSI MAX WP 001
Brand Description	Tape Brand - White Letters
Compare to	Gates Hot Air Blower; Goodyear Plicord Torrid Air; Titan Hot Air Blower; Boston Wildcat Hot Air

LENGTHS: 100 ft. lengths.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7281-1500	1½	38.1	2	2.055	52.2	97	4.0	175
7281-2000	2	50.8	2	2.562	65.1	126	6.0	175
7281-3000	3	76.2	2	3.571	90.7	200	12.0	175
7281-4000	4	102.0	2	4.614	117.2	278	16.0	175

7281

Applications

- Dry Material Unloading
- Air Compressors



WARNING! Cam and Groove Type Fittings are not recommended for use on this product when used in high temperature applications!