



MPW – 1000® Multi-Purpose Hose Series 7204

This versatile multi-purpose hose is ideal for rugged service in many industrial and high pressure steam cleaning applications. In addition to air and water service, the oil resistant tube and cover will handle a variety of acids and chemicals. Suitable for saturated steam service to 150 PSI and temperatures to 368° F. Also suitable to convey hot tar, wax and glue at 300° F continuous, 350° F intermittent.

4:1 Design factor (10:1 for 150 PSI steam applications)

>> Withstands high temperatures in multiple uses

Tube	Black Nitrile
Cover	Perforated Black Neoprene
Reinforcement	One wire braid
Temperature Range	-20°F to +300°/350°/368°F (steam) (-29°C to +149°/177°/187°C)
Branding	PARKER 7204 - MPW 1000 PSI MAX WP (DATE CODE) MADE IN USA
Brand Description	Embossed Brand
Compare to	Gates 319MB Gold Master

LENGTHS: Random lengths on 500 ft. nominal reels, 50 ft. min. length. Max. 600 ft., min. 400 ft. 5 pieces max. per reel with 50 ft. length.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7615, 7692. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

7204

Applications

- Steam Service
- Acid and Chemical Transfer
- Hot Tar, Wax and Glue

Part No.	ID (in.)	ID (mm)	Reinf. Layers	OD (in.)	OD (mm)	Approx Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP	Max. Steam WP
7204-381	3/8	9.5	1	0.781	19.8	28	5.0	1000	150
7204-501	1/2	12.7	1	0.906	23.0	34	7.0	1000	150
7204-751	3/4	19.1	1	1.187	30.1	52	9.5	1000	150
7204-1001	1	25.4	1	1.500	38.1	75	12.0	1000	150