



STINGER™ II

Mine Air & Water Hose

Series 7268

Stinger II hose is a very durable hose manufactured to handle the severe service requirements of underground mine spray service. The bright yellow MSHA cover is flame, oil and abrasion resistant. This hose is also an excellent choice for high pressure air and washdown service.

4:1 Design factor (2 in. - 3.5:1)

>> MSHA approved for mine service

Tube	Black Neoprene
Cover	Yellow NBR/PVC
Reinforcement	Wire braid
Temperature Range	-20°F to +212°F (-29°C to +100°C)
Branding	PARKER USA 7268 STINGER II™ 3/4 ID 1000 PSI MAX WP MSHA IC-123/17 B5 (DATE CODE)
Brand Description	Ink Brand - Black letter color
Compare to	Goodyear Minespray, Super Ortac; Gates 1000MP/Mine Spray; Boston Concord Yellow Jack

LENGTHS: ¾" and 1" on 500 ft. reels, 5 piece max., 50 ft. min. length. 50 ft., 100 ft., also available, 200 ft. available on quotation.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in)	ID (mm)	Reinf. Braids	OD (in)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7268-751	¾	19.1	1	1.045	26.5	36	6.0	1000
7268-1001	1	25.4	1	1.339	34.0	53	8.0	1000
7268-1251	1¼	31.8	1	1.631	41.4	66	12.0	1000
7268-1501	1½	38.1	1	1.890	48.0	86	14.0	1000
7268-2001	2	50.8	1	2.440	62.0	141	18.0	1000

7268

Applications

- Mines
- Air Tools
- Dust Suppression Systems