



YELLOW BIRD® Air & Water Hose – MSHA Series 7284

YELLOW BIRD® hose is designed for high pressure water service in underground mines. The SBR tube, wire braided construction, and nitrile/PVC cover also make it an excellent high pressure air or general purpose hose. The flame resistant yellow cover is branded with the MSHA legend.

4:1 Design factor

>> MSHA approved for mine service

Tube	Black SBR
Cover	Yellow NBR/PVC, PIN-PRICKED
Reinforcement	One or multiple wire braids
Temperature Range	-20°F to +212°F (-29°C to +100°C)
Branding	PARKER USA 7284 YELLOW BIRD® HOSE (DATE CODE) DE2 XXXX PSI MAX WP MSHA IC-123/17 - FLAME RESISTANT
Brand Description	Ink Brand - Black letter color
Compare to	Thermoid Hercules 1000; Boston Concord Yellow Jack; Gates 1000MP/Mine Spray

LENGTHS: Random lengths on nominal 500 ft. reels. 50ft. + 100ft. coils also available.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Braids	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7284-381	3/8	9.5	1	0.688	17.5	25	6.0	1500
7284-501	1/2	12.7	1	0.969	24.6	37	7.0	1000
7284-751	3/4	19.1	1	1.219	31.0	56	9.5	1000
7284-1001	1	25.4	1	1.469	37.3	69	12.0	1000
7284-1252	1 1/4	31.8	2	1.719	43.7	90	15.5	1000

7284

Applications

- Mines
- Air Tools
- Dust Suppression Systems