



MEGA BLUE/MEGA RED ORS Air & Water Hose

Series 7518 (Blue) / 7519 (Red)

Meets or exceeds RMA Grade 1, Class A Oil Resistance Standard. Specially blended tube and cover compounds provide users with the weight and flexibility of thermoplastics combined with the feel and many physical properties of rubber. Excellent for most applications where a more rugged, durable hose is required.


4:1 Design factor

>> Lightweight yet durable

Tube	Modified PVC
Cover	Rubber Modified Thermoplastic
Reinforcement	Polyester Yarn
Temperature Range	-20°F to +180°F (-29°C to +82°C)
Branding	PARKER MEGA xxxx ORS - (PRESSURE) PSI WP - (ID)" - (ID)MM - MADE IN USA
Brand Description	Ink Brand - White letter color
Compare to	Boston Ultraforce, Jason 4105

LENGTHS: 500 ft. reels. Reels are 90% one continuous length. If two pieces, lengths will be in multiples of 50 ft.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.



Applications

- Air Tools
- Water Hose

Part No.	ID (in.)	ID (mm)	Reinf. Braid	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
-250	¼	6.4	1	0.500	12.7	9	1.0	350
-375	⅜	9.5	1	0.641	16.3	12	1.5	350
-500	½	12.7	1	0.781	19.8	17	2.5	300
-625	⅝	15.9	1	0.890	22.6	20	2.8	250
-750	¾	19.1	1	1.063	27.0	26	6.0	250
-1000	1	25.4	1	1.313	33.4	35	7.0	200