



339xx

COMMERCIAL DUTY PVC Air Hose

This professional duty PVC air hose is designed to withstand working pressures up to 300 PSI. It is flexible and lightweight. Assemblies are coupled with 3/8" NPT male brass fittings each end and are equipped with PVC strain relief sleeves and descriptive hose boards.

4:1 Design factor

>> Rugged yet lightweight

Tube	PVC
Cover	Yellow PVC
Reinforcement	Polyester Yarn
Temperature Range	0°F to +130°F (-18°C to +54°C)
Branding	--- (SIZE)" ID -- (SIZE) MM --- 300 PSI WP -- MADE IN USA ---
Brand Description	Ink Brand - Black letter color
Compare to	Goodyear Pliovic GS, Jason 4103, Kentak ATH, Kuriyama HS 117, Superflex AH

LENGTHS: 90% of reels contain one continuous length. If 2 pieces, minimum length is 50 ft.

COUPLINGS: NPT brass fittings.

Part No.	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Coupling Size (in.)	Max. Rec. WP	Length	Package	Pkg. Wt.
33903	¼	6.4	0.500	12.7	¼	300	25	10/Carton	21
33904	¼	6.4	0.500	12.7	¼	300	50	5/Carton	21
33932	¼	6.4	0.500	12.7	—	300	500	Reel	44
33913	⅜	9.5	0.595	15.1	¼	300	25	10/Carton	25
33914	⅜	9.5	0.595	15.1	¼	300	50	5/Carton	25
33935	⅜	9.5	0.595	15.1	—	300	500	Reel	53

Applications

- Air Tools