



## HYDRO-AIRE™ PVC Air & Water Hose

Hydro-Aire is an extremely flexible and lightweight PVC hose designed for air and water applications.

4:1 Design factor

**>> Lightweight makes hose ideal for on-the-job use**

<b>Tube</b>	Black PVC
<b>Cover</b>	Red or Black PVC
<b>Reinforcement</b>	Polyester Yarn
<b>Temperature Range</b>	-20°F to +130°F (-29°C to +54°C)
<b>Branding</b>	SWAN HYDRO-AIRE - - - (PRESSURE) PSI WP - - - MADE IN USA - - - (SIZE) IN - (SIZE) MM
<b>Brand Description</b>	Ink Brand - White letter color
<b>Compare to</b>	Boston H275; Goodyear Pliovic Plus 250; Kentak ATL; Kuriyama K115

**LENGTHS:** 500 ft. reels. Reels are 90% one continuous length. If two pieces, lengths will be in multiples of 50 feet.

**COUPLINGS:** For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7611, 7615, 7692, 7628, 7670. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

### Red Cover

Part No.	ID (in.)	OD (mm)	Reinf. Layers	OD (in.)	OD (mm)	Aprox. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
39362	¼	6.4	2	0.500	12.7	10	2.5	250
39363	⅝	7.9	2	0.593	15.1	12	3.0	250
39364	⅜	9.5	2	0.641	16.3	14	3.5	250
39365	½	12.7	2	0.781	19.8	18	5.0	250
39366	⅝	15.9	2	0.921	23.4	22	6.5	250
39367	¾	19.1	2	1.031	26.2	27	7.5	200
39368	1	25.4	2	1.281	32.5	36	10.0	150

### Black Cover

Part No.	ID (in.)	ID (mm)	Reinf. Layers	OD (in.)	OD (mm)	Aprox. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
39382	¼	6.4	2	0.500	12.7	10	2.5	250
39383	⅝	7.9	2	0.593	15.1	12	3.0	250
39384	⅜	9.5	2	0.641	16.3	14	3.5	250
39385	½	12.7	2	0.781	19.8	18	5.0	250
39386	⅝	15.9	2	0.921	23.4	22	6.5	250
39387	¾	19.1	2	1.031	26.2	27	7.5	200
39388	1	25.4	2	1.281	32.5	36	10.0	150

3936x

3938x

### Applications

- Air Tools
- Water