



## Fire Engine Corrugated Suction Hose Series 7209

Water suction hose for use on fire engines. Rugged, heavy duty construction for long service life. Corrugated cover reduces bend resistance providing maximum flexibility.

**>> Heavy duty for long service life and dependability**

<b>Tube</b>	Black SBR
<b>Cover</b>	Black SBR
<b>Reinforcement</b>	Multiple textile plies with helix wire
<b>Temperature Range</b>	-30°F to +180°F (-34°C to +82°C)
<b>Branding</b>	None
<b>Compare to</b>	Titan Corrugated Fire Engine Suction Hose

**LENGTHS:** 10 ft. overall length including soft cuff.

**COUPLINGS:** Not available from Parker. For assembly guidelines and coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	Max. Cuff OD (in.)	Max. Cuff OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Test Pressure
7209-4502010	4½	114.3	2	5.354	136	272	14.0	200
7209-5002010	5	127.0	2	5.866	149	300	15.0	200
7209-6002010	6	152.4	2	6.850	174	380	28.0	200

7209

### Applications

- Fire Engines