



Booster 800 High Pressure Hose Series 7270

This is a heavy duty hose for high pressure chemical and water booster service on fire engines. Acceptable for short term use with Halon 1211. Tube and cover compounds are abrasion and weather resistant. Tough yet flexible, for resistance to flexing and surge loads. Meets NFPA 1961 requirements under current RMA specifications. Meets or exceeds UL92 requirements for 800 PSI Booster Hose.

4:1 Design factor

>> Durable and kink resistant

Tube	Black Neoprene
Cover	Red Neoprene
Reinforcements:	Multiple textile braids
Temperature Range	-40°F to +180°F (-40°C to +82°C)
Branding	PARKER USA 7270 HP BOOSTER 800 HOSE - 800 PSI MAX WP-3200 PSI BURST - B5 (DATE CODE)
Brand Description	Ink Brand - Black letter color
Compare to	Thermold Alarm Booster; Goodyear Fire Engine Booster

LENGTHS: Random lengths on reels. Also available in 50ft., 100ft., 150ft., and 200ft. lengths.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Braids	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7270-752	¾	19.1	2	1.173	29.8	39	7.0	800
7270-1002	1	25.4	2	1.500	38.1	59	8.0	800

7270

Applications

- Fire Engines
- Fire Suppression Systems