



Clear Vinyl Tubing – FDA & NSF

Series 7558

Lightweight, non-marking, flexible tubing made with tight tolerances. Will not support combustion. Materials comply with FDA Specifications. NSF Certified under Standard NSF-51.

4:1 Design Factor


>> Suitable for use in commercial food equipment

Tube	Clear Food Grade PVC
Temperature Range	+25°F to +150°F (-4°C to +66°C)
Branding	PARKER 7558 PVC - MAX TEMP 150F - (SIZE)" - (SIZE) MM - (PRESSURE) PSI WP - NSF-51 (LOT#) (DATE CODE) - MADE IN USA
Brand Description	Ink Brand - Black letter color
Compare to	Kentak K-9500 (Tubing); Kuriyama K010; New Age CLEARFLO.

LENGTHS: 100 ft.

COUPLINGS: For assembly guidelines and coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7558-125	1/8	3.2	1/4	6.4	2.0	1/4	65
7558-187	3/16	4.8	5/16	7.9	2.6	5/8	55
7558-250	1/4	6.4	3/8	9.5	3.2	3/4	55
7558-251	1/4	6.4	1/2	12.7	7.6	1/2	60
7558-312	5/16	7.9	7/16	11.1	3.8	3/4	50
7558-381	3/8	9.5	1/2	12.7	4.5	1 3/4	45
7558-500	1/2	12.7	5/8	15.9	5.7	1 1/4	30
7558-501	1/2	12.7	1 1/16	17.5	9.0	2	40
7558-502	1/2	12.7	3/4	19.1	13.0	1 3/4	45
7558-625	5/8	15.9	13/16	20.6	11.0	3	35
7558-626	5/8	15.9	7/8	22.2	13.0	3 3/4	40
7558-750	3/4	19.1	1	25.4	18.0	4	35
7558-1000	1	25.4	1 1/4	31.8	23.0	7 1/2	25
7558-1250	1 1/4	31.8	1 1/2	38.1	28.0	11	20
7558-1500	1 1/2	38.1	2	50.8	72.0	12	35
7558-2000	2	50.8	2 1/2	63.5	92.0	15	35



Applications

- Food Transfer
- Drain Lines
- Light Vacuum Lines
- Sight Gauges
- Low Pressure Air and Water