



Concrete Pump & Plaster Hose – 800 PSI Series 7236

Recommended for spraying wet plaster and wet or dry cement at pressures up to 800 PSI. The specially compounded tube is highly resistant to abrasive materials. Heavy wall resists kinking. Static conductive tube and cover.
3:1 Design factor

>> Withstands high working pressures

Tube	Black Natural Rubber Blend - Static Conductive
Cover	Black SBR
Reinforcement	Multiple textile plies
Temperature Range	-30°F to +150°F (-34°C to +66°C)
Branding	PARKER SERIES 7236 PLASTER & CONCRETE HOSE 800 PSI MAX WP MADE IN USA 001
Brand Description	Tape Brand - Black letters on white stripe
Compare to	Goodyear Allcrete Textile; Titan SS123/SS120

LENGTHS: 50 ft. and 100 ft.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Plies	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min Bend Radius	Max. Rec. WP
7236-125500	1¼	31.8	4	1.882	47.8	78	9.0	800
7236-150800	1½	38.1	4	2.212	56.2	101	12.0	800
7236-200800	2	50.8	4	2.762	70.2	138	24.0	800

Additional sizes available within minimum order requirements.

7236

Applications

- Spraying Wet Plaster
- Wet Cement